# NSYTBP19128T

# PC box IP66 IK08 RAL7035 Int.H175W105D80 Ext.H192W121D87 Transp.cover H20





#### Main

| Thalassa                               |
|--|
| Thalassa TBP                           |
| Multi-purpose                          |
| Industrial box                         |
| 7.56 in (192 mm)                       |
| 4.76 in (121 mm)                       |
| 3.43 in (87 mm)                        |
| 6.89 in (175 mm)                       |
| 4.13 in (105 mm)                       |
| 3.15 in (80 mm)                        |
| Wall mounted                           |
| 1 body<br>1 cover<br>4 cover screw     |
| Set of 2                               |
| One piece moulded                      |
| Low transparent cover                  |
| Plastic screws                         |
| Captive screw flat outside sealed area |
| Cover by captive screws                |
|  |

#### Complementary

| Material                    | polycarbonate                 |  |
|-----------------------------|-------------------------------|--|
| Color                       | Gray RAL 7035)<br>Transparent |  |
| Standards                   | IEC 62208<br>UL 508 A         |  |
| Product Certifications      | TÜV<br>UL                     |  |
| Electrical Insulation Class | Class II                      |  |
| Mounting location           | Outdoor                       |  |
| Net Weight                  | 0.84 lb(US) (0.38 kg)         |  |

#### Environment

| IP degree of protection             | IP66 conforming to NEMA 4.4X |
|-------------------------------------|------------------------------|
| IK degree of protection             | IK08 IEC 62262               |
| Fire resistance                     | 1760 °F (960 °C)             |
| Ambient Air Temperature for Storage | 5140 °F (-1560 °C)           |
| Operating temperature               | -13176 °F (-2580 °C)         |

#### Ordering and shipping details

| Category              | 80033-ENCLOSURE SYSTEMS POLYESTER |
|-----------------------|-----------------------------------|
| Discount Schedule     | ES1                               |
| GTIN                  | 3606480165801                     |
| Nbr. of units in pkg. | 1                                 |
| Package weight(Lbs)   | 13.40 oz (380.0 g)                |
|                       |                                   |

| Returnability     | No |
|-------------------|----|
| Country of origin | HU |

## Packing Units

| Unit Type of Package 1       | PCE                      |
|------------------------------|--------------------------|
| Package 1 Height             | 3.43 in (8.7 cm)         |
| Package 1 width              | 4.76 in (12.1 cm)        |
| Package 1 Length             | 7.56 in (19.2 cm)        |
| Unit Type of Package 2       | BB1                      |
| Number of Units in Package 2 | 2                        |
| Package 2 Weight             | 29.14 oz (826.0 g)       |
| Package 2 Height             | 3.94 in (10.0 cm)        |
| Package 2 width              | 7.87 in (20.0 cm)        |
| Package 2 Length             | 10.24 in (26.0 cm)       |
| Unit Type of Package 3       | CAR                      |
| Number of Units in Package 3 | 28                       |
| Package 3 Weight             | 27.71 lb(US) (12.568 kg) |
| Package 3 Height             | 15.75 in (40.0 cm)       |
| Package 3 width              | 16.14 in (41.0 cm)       |
| Package 3 Length             | 23.62 in (60.0 cm)       |

#### Offer Sustainability

| onor odotamability         |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACh Regulation           | ☑ REACh Declaration   |
| REACh free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS  Declaration |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | €Yes  |
| China RoHS Regulation      | <sup>™</sup> China RoHS Declaration   |
| Environmental Disclosure   | Product Environmental Profile   |
| Circularity Profile        | € End Of Life Information   |

## Contractual warranty

| Warranty  | 10 months  |
|-----------|------------|
| Wallalily | TO HIGHLIS |
|           |            |
|           | 18 months  |