



Quality Products. Service Excellence.

## Economy 2-Post Open Frame Rack *RB-2P Series*

UL2416 rated for up to 1,000 lbs (453 kg). Static Load tested to 4,000 lbs (1,814 kg).



**RACK BASICS®**




### Features:

- Rack rails are constructed in 12-gauge welded steel. Base angles are constructed in 1/4" steel plates.
- 19" EIA compliant 10-32 double-tapped rails.
  - Includes marked rack unit dividers to aid in equipment mounting.
  - Don't forget to order your **Mounting Hardware**.
- The side of the mounting rails included ganging and accessory mounting holes.
- Two (2) pairs of 5/8" spaced 10-32 threaded ground studs are integrated into the rails. Stud pairs are conveniently located across from each other inside the rail channel. For added convenience, one pair is located near the top of the rack, while the other pair is located on the lower side.
- UL Listed 2416 load rated for up to 1,000 lbs (453 kg). Static Load tested to 4,000 lbs (1,814 kg).
- Finished in smooth RAL9005 black powder coating.
- Rails and base are packaged in cardboard to prevent freight damage.
- TAA-compliant for GSA Schedule purchases.
- RoHS Compliant.
- Manufactured in North America within an ISO 9001:2015 certified facility.

Part of the Rack Basics® line of economy rack solutions.

### Gallery



### Accessories

- High-Density Vertical Finger Manager with Slam-Latching Door
- Vertical Rack Cable Manager with Door
- Top Wire Management
- Horizontal Finger Cable Manager
- Universal Rack Shelf
- Two Post Variable Depth Shelf
- Two Post Mounting Keyboard & Equipment Shelf
- 2-Post Rack Low Profile Dolly
- Rack Isolation Kit
- 10-32 Mounting Hardware
- Rackmount Adjustable Angle Bracket
- Vertical Finger Cable Manager with Door
- Vertical Cable Manager Extensions
- Horizontal Ring Cable Manager
- Rack Panels
- Two Post Mounting Adjustable Shelf
- Two Post Centered Shelf
- Two-Post Extension Support Bracket
- Open Frame Rack and Rack Cabinet Joining Kit
- Grounding & Bonding
- PDUs and Outlet Strips

Part No.	Overall Dimensions			Rack Units	Mounting Dimensions		Optional Vertical Cable Manager
	Height	Width	Depth		Height	Width	
RB-2P24	48.12	20.46	15.00	24U	42.16	19.00	RB-VCM24
RB-2P77	83.12	20.46	15.00	44U	77.12	19.00	RB-VCM44
RB-2P84	90.12	20.46	15.00	48U	84.16	19.00	RB-VCM48

Tags: **Relay Rack, H-Frame, Server Rack, Equipment Rack, Network Rack, Skeleton Rack, Telco Rack,** *Data subject to change without notice*  
**Two-Post Rack**

© 2023. Hammond Manufacturing Ltd. All rights reserved.