

VLM10555T-1R8M8R8-2

Applications		Commercial Grade
Feature	Wire Wound	Wire Wound
	Shield	Magnetic Shield
	Ferrite Core	Ferrite Core
Series	VLM Series / VLM10555-2 Type	
Status	PROD (Recommendation is available)(Recommended Alternate Part Number:Please get contact with TE	





Size	
Length(L)	10.30mm +0.20mm
Width(W)	10.60mm +/-0.20mm
Thickness(T)	5.40mm +/-0.20mm
Recommended Land Pattern (A)	2.60mm Nom.
Recommended Land Pattern (B)	3.40mm Nom.
Recommended Land Pattern (C)	3.00mm Nom.
Recommended Land Pattern (D)	6.10mm Nom.
Recommended Land Pattern (E)	1.90mm Nom.
Recommended Land Pattern (F)	1.80mm Nom.

Electrical Characteristics				
Inductance	1.8uH +/-20% at 100kHz			
Rated Current (L Change) [Max.]	18A (25% Down)			
Rated Current (Temperature Rise) [Typ.]	8.8A (40degC Rise)			
Rated Current (Temperature Rise) [Max.]				
DC Resistance [Nom.]	5.6mΩ			
DC Resistance [Max.]	6.44mΩ			

Other					
Operating Temp. Range (Including Self-Temp. Rise)	-40 to 125degC				
Soldering Method	Reflow, Iron Soldering				
AEC Q200	No				
Packing	Blister (Plastic)Taping [330mm Reel]				
Package Quantity	500Pcs Min.				
Weight	1.7g				

•This PDF document was created based on the data listed on the TDK Corporation website. •All specifications are subject to change without notice. **⊗TDK** Inductors(Coils)

VLM10555T-1R8M8R8-2

Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)







VLM10555T-1R8M8R8-2





VLM10555T-1R8M8R8-2

VLM10555T-1R8M8R8-2

•This PDF document was created based on the data listed on the TDK Corporation website. •All specifications are subject to change without notice.



VLM10555T-1R8M8R8-2

Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)



Temperature Characteristic	
no data available	



VLM10555T-1R8M8R8-2(Amb. Temp. = 20degc)

This PDF document was created based on the data listed on the TDK Corporation website.All specifications are subject to change without notice.