





NMOSC SERIES

High Performance NMO Shock Absorbing Mount 0-6 GHz

This shock absorbing permanent NMO mount provides an extended frequency range up to 6 GHz. This allows antennas in frequency ranges above traditional LMR195 equivalent frequencies to be deployed.

FEATURES AND BENEFITS

- Integrated shock absorbing bushing helps resist vehicle damage resulting from incidental contact with antenna base
- Ideal solution for vehicles requiring high clearance due to overall vehicle height
- Electroless nickel plated zinc material resists corrosion

ELECTRICAL SPECIFICATION

Operating Frequency (GHz)

٠	Gold plated contact for superior conductivity and
	high-performance up to 6 GHz

- Available coax options: LMR195 equivalent, 17' RG58A/U, or 17' RG58U
- Available in other coax lengths and connector options

0-6

MECHANICAL SPECIFICATION		
Weight	Varies depending on cable type and length	
Mount Type	¾in., NMO	
Hardware	O-Ring and NMO Ring adapter included	
Installation Hole Size -inches	3/4	

ENVIRONMENTAL SPECIFICATION			
Operating Temperature - °C (°F)	-40° to +85°C (-40° to +185°F)		
Material Substance Compliance	RoHS		
IP Rating	IP67 sealed at mount surface. Fully IP67 rated when terminated to antenna with IP67 provisions		

CONFIGURATION

PART NUMBER	CABLE LENGTH	CONNECTOR
NMOSCFMUHM518	Mini UHF Male	17 ft. RG-58A/U
NMOSCFSMAM518	SMA Male	17 ft. RG-58A/U
NMOSCFTNCM518	TNC Male	17 ft. RG-58A/U
NMOSCFRPSMM518	RP-SMA Male	17 ft. RG-58A/U
NMOSCFFMEM518	FME Male	17 ft. RG-58A/U
NMOSCFUHFM518	UHF PL259 Male	17 ft. RG-58A/U
NMOSCF518	No Connector	17 ft. RG-58A/U
NMOSCGMUHM518	Mini UHF Male	17 ft. RG-58/U
NMOSCGSMAM518	SMA Male	17 ft. RG-58/U
NMOSCGTNCM518	TNC Male	17 ft. RG-58/U
NMOSCGRPSMM518	RP-SMA Male	17 ft. RG-58/U
NMOSCGFMEM518	FME Male	17 ft. RG-58/U
NMOSCGUHFM518	UHF PL259 Male	17 ft. RG-58/U
NMOSCG518	No Connector	17 ft. RG-58/U
NMOSCNMUHM518	Mini UHF Male	17 ft. Low Loss 195
NMOSCNSMAM518	SMA Male	17 ft. Low Loss 195
NMOSCNTNCM518	TNC Male	17 ft. Low Loss 195
NMOSCNRPSMM518	RP-SMA Male	17 ft. Low Loss 195
NMOSCNFMEM518	FME Male	17 ft. Low Loss 195
NMOSCNUHFM518	UHF PL259 Male	17 ft. Low Loss 195
NMOSCN518	No Connector	17 ft. Low Loss 195
NMOSCAA518	No Connector	17 ft. Laird Teflex
NMOSCW518	No Connector	17 ft. Laird High Performance Teflex
NMOSC	No Connector	No Cable

te.com

TE, and TE connectivity (logo) are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warrantied to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

08/22 Original

DATA AND DEVICES / NMOSC SERIES

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31(0)73-6246-999
China:	+86 (0) 400-820-6015



