Rev: 2023-04-21

WBASLP

Static Dissipative Waste Basket Liners

Use ESD trash liners to dispose of waste materials that pose a static damage threat.

The WBASLP Anti-Static Trash Can Liner is ideal for clean rooms, manufacturing, inspection, quality control and research industries where static control is crucial. The average surface resistivity of the liners less than or equal to 10^11 ohms per square. Static decay rate is less than two seconds per Mil-B-81705BType II-Federal test method 101C method 4046. The translucent pink trash liner has a capacity of:

- 7-10 gallon For use with the <u>WBAS28 waste basket</u>.
- 22 gallon For use with the <u>WBAS90 trash can</u>
- 44 gallon For use with the WBAS180 trash can

Meets or exceeds requirements of ANSI ESD-S20.20.





Product Specifications

Basic material Single layer of non-amine polyethylene

Color Translucent Tinted Pink

Thickness 2 mil (WBASLP), 4 mil (WBAS22LP) 4 mil

(WBAS44LP)

Size 24" x24", 30"x36", 40"x46"

Tensile Strength 2000 to 3000 PSI

Tearing Strength 65 to 450 lbs. per inch

Surface

Resistivity

 $\leq 10^{11}$ OHMS/Sq.

Static Decay

Rate

5kV- 0Volts < 2 seconds

Shelf Life Perm

Permanently anti-static under normal

storage conditions

Product Number

<u>Item Number</u> <u>Description</u>

WBASLP: Anti-Static Trash Can Liner, Dissipative,

7 - 10 Gallon, Pink, 24"x24"x2mil ُ

WBAS22LP: Anti-Static Trash Can Liner, Dissipative, 22 Gallon, Pink, 30"x36"x4mil

WBAS44LP: Anti-Static Trash Can Liner, Dissipative,

44 Gallon, Pink, 40"x46"x4mil



For use with Transforming Technologies ESD trash cans

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.