

Humidity Indicator Cards and Desiccant: Product Selection Guide

SCS Humidity Indicator Cards (HIC) are printed with moisture sensitive spots which change color from blue to pink when exposed to a relative humidity level. The HIC is typically used with Desiccant inside a Moisture Barrier Bag to protect static and moisture sensitive components noting the highest relative humidity level exposure. SCS manufactures <u>Moisture Barrier</u> <u>Bags</u> with different laminates having different moisture vapor transmission rates. SCS Dri-Shield® bags are designed to be used with Desiccant and an HIC for packaging surface mount devices (SMD) trays and reels. The bags are sealed, including being vacuum sealed, containing the SMD or other content along with the Desiccant and selected HIC. The HIC will note the highest relative humidity exposure, so the user can determine if baking the devices is required. SCS recommends the user follow procedures defined in IPC/JEDEC J-STD-033. SCS manufactures MBB and HIC products in Sanford, North Carolina.

SCS Desiccant pouches absorb moisture that passes through the bag laminate. Desiccant is packed inside Tyvek[®] white non-woven plastic or brown kraft paper pouches, and is shipped in sealed pails or drums. The amount of desiccant to use is dependent on the interior surface area of the bag; see <u>EIA-583</u>, <u>Table 1</u>, SCS Desiccant is manufactured in North America.

Humidity Indicator Cards

| Item Number | Size | Number of Spots | Relativity Humidity Levels | Quantity per Metal Can |
|-------------------|------------------|-----------------|----------------------------|------------------------|
| 51060HIC125 | 2" x 3" | 3 | 5/10/60 | 125 |
| 51015HIC125 | 2" x 3" | 3 | 5/10/15 | 125 |
| <u>3HIC125</u> | 2" x 3" | 3 | 30/40/50 | 125 |
| <u>4HIC100</u> | 3" x 2" | 4 | 10/20/30/40 | 100 |
| <u>6HIC200</u> | 1 9/16" x 4 3/4" | 6 | 10/20/30/40/50/60 | 200 |
| <u>3HIC125-CF</u> | 2" x 3" | 3 | 30/40/50 | 125 |
| 51015HIC125-CF | 2" x 3" | 3 | 5/10/15 | 125 |
| 51060HIC125-CF | 2" x 3" | 3 | 5/10/60 | 125 |
| 6HIC200-CF | 1 9/16" x 4 3/4" | 6 | 10/20/30/40/50/60 | 200 |



Indicator Card

Desiccant in White Non-Woven Tyvek[®] Pouch

| Item Number | Size | Pouch | Pouches per Container |
|--------------------|-----------------|----------|--------------------------|
| 1/6PLDES1200 | 2.125" x 2.125" | 1/6 Unit | 1200 |
| <u>1/3PLDES700</u> | 2.125" x 2.5" | 1/3 Unit | 700 |
| <u>1/2PLDES550</u> | 2.125" x 2.875" | 1/2 Unit | 550 |
| 1PLDES300 | 3" x 4.5" | 1 Unit | 300 |
| 1PLDES1800 | 3" x 4.5" | 1 Unit | 1800 |
| 2PLDES150 | 5" x 4.5" | 2 Unit | 150 |
| 2PLDES800 | 5" x 4.5" | 2 Unit | 800 |
| 4PLDES500 | 5" x 6.25" | 4 Unit | 500 |
| 8PLDES300 | 4.5" x 8.5" | 8 Unit | 300 |
| 16PLDES150 | 4.5" x 11" | 16 Unit | 150 |

Desiccant in Brown Kraft Paper Pouch

| Item Number | Size | Pouch | Pouches per Container |
|-------------------|---------------|----------|--------------------------|
| <u>1/2KDES550</u> | 2.375" x 3.5" | 1/2 Unit | 550 |



Desiccant in Tyvek[®] Pouch



Desiccant in Kraft Pouch

RoHS 3, REACH and Conflict Minerals Statement

None of the RoHS 3 restricted materials, or REACH substances of very high concern as of 2017/07/07, or Toxic in Packaging substances are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See <u>SCS Warranty, Limitation of Liability and Remedies</u>



926 JR Industrial Drive, Sanford, NC 27332 East Coast: 919-718-0000 | West Coast: 909-627-9634 StaticControl.com

