T G			0	₩ >		
A						4
ω			LAYOUT SHOWN AS EXAM	MPLE		9
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
 -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer Contact Plating : Gold over copper Alloy 0.8µm minimum 	DimNominalØS44.9 MaxZ31 MaxVV THREADM34x1-6g		SOURIAU shall not be liable for any no due to a use of the Products which the Specifications issued by either of th (professional recommendation Country FR	does not comply with e Parties or by a third party]	2
-Durability : 500 Mating cycles -Delivered without Souriau contacts		PN: 8D523W06PDL				
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 07-10-2016 ISS DATE Designed By:	First Release Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	,
		TITLE Aluminium Plug 8D series				
BASIC SERIES: 8D 5 - 23 W 06 → SHELL TYPE : Plug with RFI Shielding	P D L Delivered W/O Contacts	SCALE -	General linear Tolerances: ±	NPRDS / PROJECT 859 This document is the pro	operty of	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 23	ORIENTATION : D CONTACT TYPE : PIN(500 Matings)	- SOURIAU VV VV.SOURIAU.COIVI it must not be reproduced or			ced or	
PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 23-06	FORMAT A3	SOURIAU D	PRG N°	SHEET	
H G	F E		8D523W06	B A	1/2	

F	Т	۵	п	m	D	0
		Contact Layout				
4		06				
		0				
	é	5#8 Concentric Twinax Service M				
		23-06]			
	Ctc	X Y	-			
	A	0 9.24				
	В	8.81 2.87				
	C	5.43 -7.49]			
ယ	D	-5.43 -7.49				
	E	-8.81 2.87	-			
	F	0 0				
	_					
						SOURIAU shall not be liable for an due to a use of the Products w
						the Specifications issued by either o
						(professional recommenda
N						Count
						PN: 8D523V
					A 07-10-20	16 First Release
_					ISS DATE	
					Designed By:	Date:
					TITLE	Alumir
					SCALE	General linear
<u> </u>					NA	t
					SOURIA	U WWW.SOURIAU.C
					FORMAT	SOURIAU
					A3	8D523W
L	Н	G	F	E	D	C
		· · · · · · · · · · · · · · · · · · ·		· • •		· · · · ·

	Φ		A			
					4	
					3	
whic r of tl datio ntry R	n, technical n	mply with by a third party			2	
		CUSTOMER	DRAWING	MOD N°		
inium Plug 8D series						
r	NPRDS / PROJECT					
859						
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
U	DRG N°			SHEET		
<u>V0</u> 6	6PDL-C			2/2		
	В		А			