Pliers

Pliers

Introduction	E.2
VDE-insulated combination pliers	E.3
VDE-insulated diagonal-cutting pliers	E.4
VDE-insulated telephone pliers	E.5
VDE-insulated flat- and round-nose pliers	E.6
ESD pliers	E.8

Е

Pliers

Pliers

Е

Working on live systems calls for special safety procedures and special tools specially produced and tested for such applications.

Weidmüller can provide users with a complete range of pliers complying with national and international testing standards. All Weidmüller pliers are produced and tested to DIN EN 60900.

Their ergonomic design fits snugly in the hand, resulting in a more natural, non-fatiguing hand position so you don't catch your fingers.





VDE-insulated combination pliers

up to 1000 V (AC) and 1500 V (DC) protective insulation to IEC 900, DIN EN 60900

- drop-forged from high-quality special tool steels
 safety handle with ergonomic and non-slip TPE VDE sleeve
- made from shockproof, heat-and cold-resistant, not readily flammable, cadmium-free TPE (thermoplastic elastomer)
- elastic grip zone and hard core
- polished surface
- nickel-chromium electrogalvanised coating protects against corrosion

KBZ 160 / KBZ 180 / KBZ 200

Combination pliers



Combination pliers acc. to DIN ISO 5746

- With opening gap (see diagram)
- Foil and sheet up to a thickness of 2.5 mm can be gripped with the tip
- When thickness does not exceed 2.5 mm, the gripping force pulls the workpiece towards the joint
- Extra-long cutter for ribbon and round cables
- For cutting soft and hard wire

KBZ 160

1.8

60

160

230

• Cutting edges inductively hardened to approx. 60 HRC



Heavy-duty combination pliers (telephone pliers)



Telegraph pliers (combination pliers), acc. to DIN 5746

- Heavy-duty model for tough demanding jobs
- Extra-long cutter for ribbon and round cables
- For cutting soft and hard wire
- Cutting edges inductively hardened to approx. 60 HRC



KBZ 180

2.5

28

60

180

290

(MH) medium-hard wire; (H) hard wire; (P) piano wire

KBZ 200

2.5

60

200

362

3



Technical data

Cutting performance	
Conductor diameter, max. (H)	mm
Conductor diameter, max. (MH)	mm
Tool data	
Cutter hardness	HRC
Total length	mm
Weight	g
Note	

Ordering data

-	
	/ersion

Туре	Qty	Order No.
KBZ 160	1	9046280000
KBZ 180	1	9046290000
KBZ 200	1	9046300000

KBZI 2	200
2.5	
3	
60	
200	
412	
(MH) m	edium-hard wire; (H) hard wire; (P) piano wire

Туре	Qty	Order No.
KBZI 200	1	9046430000

Note

Pliers

VDE-insulated diagonal-cutting pliers

up to 1000 V (AC) and 1500 V (DC) protective insulation to IEC 900, DIN EN 60900

- drop-forged from high-quality special tool steels
 safety handle with ergonomic and non-slip TPE VDE sleeve
- made from shockproof, heat-and cold-resistant, not readily flammable, cadmium-free TPE (thermoplastic elastomer)
- elastic grip zone and hard core
- polished surface
- nickel-chromium electrogalvanised coating protects against corrosion

KSE 160 / KSE 200 / SE TOP

Professional diagonal-cutting pliers for piano wire

SE HD 140 / SE HD 160 / SE HD 180

Diagonal-cutting pliers for hard wire



Diagonal-cutting pliers, acc. to DIN ISO 5749

- Cutting edges inductively hardened to approx. 64 HRC
- For cutting soft wire and piano wire

KSE 160 - KSE 200

- Optimized transmission of force
- Optimized precision cutting edge

SE TOP

• With inlaid joint

• Extra-fine precision cutting edge



Diagonal-cutting pliers, acc. to DIN ISO 5749

- With inlaid joint
- With precision cutting edges
- Cutting edges inductively hardened to approx. 62 HRC
- Special tool steel





Technical data

Cutting performance	
Conductor diameter, max. (H)	mm
Conductor diameter, max. (MH)	mm
Conductor diameter, max. (P)	mm
Tool data	
Cutter hardness	HRC
Total length	mm
Weight	g
Note	

KSE 160	KSE 200	SE TOP
2.5	3	2.5
3.5	4.2	3.5
2	2.5	2
64	64	64
160	200	160
243	325	251
(MH) medium-ha	rd wire; (H) hard wire; (P)	piano wire

SE HD 140	SE HD 160	SE HD 180
2	2.3	3
2.8	3	3.8
1.4	1.6	1.8
62	62	62
140	160	180
203	253	291
(MH) medium-hard	wire; (H) hard wire; (P) p	iano wire

Ordering data

Version

Note

 Type
 Oty
 Order No.

 KSE 160
 1
 9046410000

 KSE 200
 1
 9046420000

 SE TOP
 1
 9046340000

Туре	Qty	Order No.
SE HD 140	1	9046310000
SE HD 160	1	9046320000
SE HD 180	1	9046330000

Pliers

VDE-insulated telephone pliers

up to 1000 V (AC) and 1500 V (DC) protective insulation to IEC 900, DIN EN 60900

- drop-forged from high-quality special tool steels
 safety handle with ergonomic and non-slip TPE VDE sleeve
- made from shockproof, heat-and cold-resistant, not readily flammable, cadmium-free TPE (thermoplastic elastomer)
- elastic grip zone and hard core
- polished surface
- nickel-chromium electrogalvanised coating protects against corrosion

FRZ SG 160 / FRZ SG 200

Bent half-round-nose pliers with cutter (telephone pliers)



Bent telephone pliers with cutter acc. to DIN ISO 5745

- Half-rounded jaws
- Serrated gripping surfaces
- Tip bent at 45°
- Cutting edges inductively hardened to approx. 60 HRC
- Special tool steel

FRZ S 160 / FRZ S 200

Half-round-nose pliers with cutter (telephone pliers)



Telephone pliers with cutter to DIN ISO 5745

- Half-rounded jaws
- Serrated gripping surfaces
- Cutting edges inductively hardened to approx. 60 HRC
- Special tool steel





Technical data

Cutting performance	
Conductor diameter, max. (H)	mm
Conductor diameter, max. (MH)	mm
Tool data	
Cutter hardness	HRC
Total length	mm
Weight	g
Note	

Ordering data

Varaia	-
Versio	

FRZ SG 160	FRZ SG 200
1.6	1.8
2.5	2.8
60	60
160	200
162	207
(MH) medium-hard wir	e; (H) hard wire; (P) piano wire

Туре	Qty	Order No.
FRZ SG 160	1	9046390000
FRZ SG 200	1	9046400000

FRZ S 160	FRZ S 200
1.6	1.8
2.5	2.8
60	60
160	200
170	224
(MH) medium-hard wire	e; (H) hard wire; (P) piano wire

Type Qty	,	Order No.
FRZ S 160 1		9046370000
FRZ S 200 1		9046380000

Note

Pliers

Ε

VDE-insulated flat- and round-nose pliers

up to 1000 V (AC) and 1500 V (DC) protective insulation to IEC 900, DIN EN 60900

- drop-forged from high-quality special tool steels
 safety handle with ergonomic and non-slip TPE VDE sleeve
- made from shockproof, heat-and cold-resistant, not readily flammable, cadmium-free TPE (thermoplastic elastomer)
- elastic grip zone and hard core
- polished surface

Pliers

E

 nickel-chromium electrogalvanised coating protects against corrosion

FZ 160



Flat-nose pliers acc. to DIN ISO 5745

- Serrated gripping surface
- With long jaw



Round-nose pliers acc. to DIN ISO 5745

- Serrated gripping surface
- With long jaw







Technical data

Tool data	
Total length	mm
Weight	g
Note	

Ordering data

Va		
Ve	rs	101

FZ 160			
160			
163			

Туре	Qty	Order No.
FZ 160	1	9046350000

RZ 160		
160		
153		

Туре	Qty	Order No.
RZ 160	1	9046360000

Note

ESD pliers

Weidmüller ESD pliers can be used with precision and safety when working with sensitive electronics. Electrostatic charging is prevented by the special handle material.

Electrostatic discharges (ESD) present a danger to electronics that should not be underestimated. The transferral or discharge of an electrostatic charge can cause significant damage. Charges smaller than 100 volts can cause damage to sensitive components. However, ESD with voltages under 2000 volts can not be felt by humans. When working with components which are particularly sensitive to electrostatic discharges, you need an electrostatic-free work environment and the properly designed tools. The ESD pliers are particularly suited for use with electronics, including electronic switches and components, as well as with precision mechanics. All pliers feature an ESD-protected two-coloured double-component plastic hand grip. The grip material in use complies with all of the requirements for ESD hand-tool protection for working with ESD-sensitive components.

The 120 mm-long ESD pliers are available individually or as part of a four-piece set: diagonal-cutting pliers, angle-cutting pliers, with pointed head, flat-nose pliers and snipe-nosed pliers. ESD pliers are not appropriate for working with live components or component assemblies.



SEE ESD 120

Electronic ESD diagonal-cutting pliers with pointed head

- Hard wire (spring wire or steel nails): 0.4 mm/AWG 26
- Semi-hard wire (iron or nails): 1.0 mm/AWG 18
- Soft wire (copper or aluminium): 1.5 mm/AWG 15

Ordering data

Туре	Qty	Order No.
SEE ESD 120	1	9205130000

Technical data

Weight 90 g



Е

SEE ESD 125 Electronic ESD diagonal-cutting pliers with oval head

- Semi-hard wire (iron or nails): 0.8 mm/AWG 20
- Soft wire (copper or aluminium): 1.5 mm/AWG 15

Туре	Qty
SEE ESD 125	1

Order No. 9204750000

Our law Ma

Technical data

Ordering data

Weight 90 g



FZE ESD 130 Ordering data Electronic ESD flat-nosed pliers

Type	QLY	Order No.
FZE ESD 130	1	9204760000

Technical data

Weight 90 g



SZE ESD 130

Electronic ESD Snipe-nosed pliers

Ordering data

Туре Qty Order No. SZE ESD 130 9204770000

90 g

Technical data

Weight



ESD pliers

SVSE ESD 130 Electronic ESD angle -cutting pliers

• Hard wire (spring wire or steel nails): 0.6 mm/AWG 22

- Semi-hard wire (iron or nails):
- Sering and wire (ron or hairs).
 1.0 mm/AWG 18
 Soft wire (copper or aluminium):
 1.2 mm/AWG 15

Ordering data

Туре	Qty	Order No.
SVSE ESD 130	1	9205140000

Technical data

Weight 90 g



SUPER CUT	
Electronic diagonal-cutting pliers	
 Soft wire (copper or aluminium): 1.2 mm/AWG 15 	

|--|

Qty 1	Order No. 920515000
1	920515000
a	
	q



Г	-	-	
I	F		
h	-	-	

Pliers

KOF	SET	ESD
-----	-----	-----

Electronic ESD case set

Contents:

- Diagonal-cutting pliers
- Snipe-nosed pliers
- Flat-nose pliers
- Angle-cutting pliers

Ordering data

Qty	Order No.
1	9205210000
	Qty 1

Technical data

Weight 547 g

