

5.8 mm cam with 20 m fiberglass-reinforced probe—QVGA via macro short focus

P/N: VSC58-20M

Copyright

© 2014, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: VSC58-20M

Release:

Commit: 18096 Language: en-US Modified: 2014-10-02 Formatted: 2014-10-02

Corporate Headquarters

FLIR Systems, Inc. 27700 SW Parkway Ave. Wilsonville, OR 97070

USA

Telephone: +1-503-498-3547

Website

http://www.flir.com

Customer support

http://support.flir.com

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



| Part No. | VSC58-20M |
|-------------------------------|---|
| General information | |
| Short description | 5.8 mm cam with 20 m fiberglass-reinforced probe—QVGA via macro short focus |
| Compatible main unit | VS70 |
| Integrated handset | No |
| Wireless capabilities | N/A |
| Compatible wireless handset | With optional VST |
| Compatible detachable cameras | N/A |
| Warranty | 2 years |
| Camera specifications | |
| Articulation | No |
| Diameter | 5.8 mm |
| Front camera focal length | 20–60 mm |
| Front camera field of view | 56° |
| Front camera resolution | QVGA (320 × 240) pixels |
| Probe length | 20 m |
| Video format | NTSC |
| Brightness control | Manual with variable options |
| Lamp type | LED |
| Power system | |
| Power requirements | N/A |
| Environmental data | |
| Operating temperature | -10 to 50°C (14-122°F) |
| Operating humidity | 80% maximum |
| Storage temperature | -40 to 80°C (-40 to 176°F) |

1 (2) www.flir.com



5.8 mm cam with 20 m fiberglass-reinforced probe—QVGA via macro short focus

P/N: VSC58-20M

© 2014, FLIR Systems, Inc. #VSC58-20M; r. /18096; en-US

| Physical data | |
|--|---|
| Weight | See shipping information |
| Dimensions $(H \times W \times L)$ | See shipping information |
| Material | PC-ABS, rubber hand grip, nylon strap |
| Color | Gray, black |
| Shipping information | |
| Packaging type | Brown shipping box |
| Packaging contents | Brown shipping box, hardcase, camera, camera attachments: mirror, anti-snag tip, magnet |
| Packaging weight | 4 kg |
| Packaging dimensions $(H \times W \times L)$ | 45 cm × 37 cm × 17 cm |
| Carton weight | 9 kg |
| Carton dimensions (H × W × L) | 39 cm × 36 cm × 47 cm |
| Carton quantity | 2 |
| EAN-13 | 7332558007822 |
| UPC-12 | 793950406007 |
| Country of origin | TW |
| Tariff code | 9013909000 |
| Technical support | |
| Website | http://support.flir.com |
| E-mail | T&Msupport@flir.com |
| Phone | 855-499-3662 |
| Repairs | repair@flir.com |

2 (2) www.flir.com