



POL	MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGTH
8	1200660479	888033P02M010	1.0M +55.6 -0 [3.27' +2.19" -0]

CONNECTOR SPECIFICATION:

VOLTAGE RATING	30 VAC/36 VDC
AMPERAGE RATING	2 AMPS
PROTECTION CLASS	IP68
OPERATING TEMPERATURE	-30°C TO 80°C
UL CERTIFICATIONS	NOT APPLICABLE
CSA CERTIFICATIONS	NOT APPLICABLE

ITEM	COMPONENT	MATERIAL	FINISH
7	LABLE	MYLAR	BLACK/YELLOW
6	O-RING	VITON	RED
5	COUPLER	BRASS	TEFLON/NICKEL
4	SOCKET/PIN CONTACT	BRASS GOLD	CuZn Ni/Au
3	INSERT	PUR	BLACK
2	OVERMOLD	POLYURETHANE (PUR)	BLACK
1	CABLE- 0.25 ² /24 AWG (COPPER STRANDING) 8 CONDUCT. 300V	JACKET: PUR/PVC INSUL.: POLYPROP	JACKET: BLACK

DESCRIPTION EC NO.: WEU2010-0325 DRWN: LSTEMMLE 2010/02/03 CHK'D: NS 2010/02/03 APPR: FPACHER 2010/02/04	QUALITY SYMBOLS ▽ = 0 ▽/C = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 1:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
		4 PLACES ±---	±---	DRAWN BY LSTEMMLE	DATE 2010/02/03	MICRO-CHANGE CORDSET 8 POL. FE 90/ MA 90 24/8 BLACK PUR/PVC CABLE			
		3 PLACES ±---	±---	CHECKED BY RE	DATE 2010/02/04				
		2 PLACES ±---	±.01	APPROVED BY FPACHER	DATE 2010/02/04	MOLEX INCORPORATED			
1 PLACE ±0.3	±---	MATERIAL NO. SEE TABLE		DOCUMENT NO. SD-120066-035	SHEET NO. 1 OF 1				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					