

PKG.M0.4SL.LG

SUMMARY

Wires

Low voltage

4

C

Image is for illustrative purpose only

Series	1P	
Termination type	Female solder	
IP rating	50	
AWG wire size	22.00 - 0.00	
Cable Ø	0.00 - 0.00 mm	
Status	active	
Matching parts	PAG.M0.4SL.AC52G	

Download Request a quote Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model	PK*: Fixed receptacle with two nuts (back panel mounting)
Keying	1 key (alpha=0; Plug: male contact; Receptacle: female contact)
Housing Material	PEI (Polyetherimide), gray
Variant	G : Gray front nut
Weight	4.79 g

Performance

Configuration	1P.M04 : 4 Low Voltage
Insulator	L: PEEK (UL 94 / V-0/1.5)
Rated Current	8 Amps

Specifications

Contact Type: Solder Contact Dia.: 0.9 mm (0.0354in) Bucket Dia.: 0.8 mm (0.031in) Max. Solid Conductor: 0.34 mm² (AWG 22) Max. Stranded Conductor: 0.34 mm² (AWG 22) R (max): 4.5 mOhm Test voltage (kV rms) Contact-contact: 1.2


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


Air clearance min.: 1.2 mm Creepage distance min.: 1.2 mm

Others

Endurance (Shell): >2000 mating cycles Temp (min / max): -50°C / +170°C F ret (min): 50 N F ret (max): 150 N Steam sterilization: > 100 times (with potting on rear connection)

DRAWINGS







Dimensions

	А	Ν	a
mm.	19.5	20.5- 22.2	0-4.5
in.	0,77	0,81	0,00

RECOMMENDED BY LEMO

Tools

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.