Data Sheet



Coaxial Panel Connector 22_MCX-50-0-2/111_N

Description

Straight bulkhead receptacle jack

Interface standards IEC 60169-36_CECC 22220



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \, \Omega \\ \text{Interface frequency max.} & 6 \, \text{GHz} \end{array}$

Mechanical Data

Number of matings 500
Weight 0.0015 kg

Environmental Data

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Fastening nut	Brass	Gold Plating (Nickel underplated)
Washer	Bronze	Gold Plating (Nickel underplated)

Related Documents

Outline drawing DOU-00010854
Catalogue drawing DCA-00010691
Mounting hole DOU-00008855

Ordering Information

 Bulk 100 pcs package
 22_MCX-50-0-2/111_NH

 Single package
 22_MCX-50-0-2/111_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.