

9200FR-A

FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: 9200FR-A**Other Means of Identification:** Flame Retardant Structural Epoxy Adhesive (Part A)**Related Part #** 9200FR-25ML, 9200FR-50ML

Recommended Use and Restriction on Use

Use: Epoxy adhesive resin for use with hardeners**Uses Advised Against:** Not for use as a spray coating

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADAMG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA**TEL** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**TEL** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** info@mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

9200FR-A
FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE
Section 2: Hazard(s) Identification
Classification of Hazardous Chemical
GHS Categories

Criteria		Category	Signal Word	Pictograms
Sensitization	Skin	1	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Skin Irritation		2	Warning	Exclamation
Acute Toxicity	Oral	4	Warning	Exclamation
Reproductive Toxicity		2	Warning	Health
Hazardous to the Aquatic Environment	Chronic	2	<i>none</i>	Environment

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	WARNING
Pictograms	Hazard Statements
	H319: Causes serious eye irritation H315: Causes skin irritation H317: May cause an allergic skin reaction H302: Harmful if swallowed
	H361: May damage fertility or the unborn child if swallowed
	H411: Toxic to aquatic life with long lasting effects

Section continued on the next page

9200FR-A
FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE
Continued...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P201, P202	Obtain special instructions before use. Do not handle all safety precautions have been read and understood.
P261	Avoid breathing fumes and vapors.
P280	Wear protective gloves and eye protection.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
Response	Precautionary Statements
P308 + P313	IF exposed or concerned. Get medical advice or attention.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P301 + P312, P330	IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. Rinse mouth.
P391	Collect spillage.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

9200FR-A
FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE
Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	33%
21645-51-2	aluminum trihydrate	20%
68333-79-9	ammonium polyphosphate	19%
25085-99-8	bisphenol-A epoxy resin (reaction product) ^{a)}	19%
138265-88-0	zinc borate	6%
60506-81-2	dipentaerythritol pentaacrylate	2%

a) Average molecular weight of ≤ 700

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>redness, irritation, pain</i>
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
IF ON SKIN	P302 + P352, P333 + P313, P362 + P364
Immediate Symptoms	<i>redness, irritation, dry skin, allergic contact dermatitis</i>
Response	Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse.
IF INHALED	P304 + P340
Immediate Symptoms	<i>cough, irritation of the respiratory track</i>
Response	Remove person to fresh air and keep comfortable for breathing.

Section continued on the next page

9200FR-A**FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE***Continued...*

IF SWALLOWED	P301 + P330 + P331, P312, P308 + P313
Immediate Symptoms	<i>abdominal discomfort, nausea, vomiting</i>
Response	Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor if you feel unwell. IF exposed or concerned. Get medical advice or attention.

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
Specific Hazards	Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires. Inhalation of zinc oxide and aluminum oxide fumes may cause metal fever and irritate the respiratory tract. The flu-like symptoms of metal fever may be delayed, occurring 4 to 12 hours after exposure. Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO,CO ₂), ammonia, aluminum oxides, zinc oxides and other toxic fumes.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

9200FR-A**FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE****Section 6: Accidental Release Measures**

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing the fumes and vapors. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Contain with inert and non-flammable absorbent such as soil, sand, or vermiculite.
Cleaning Methods	Collect liquid in a sealable, chemical-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Use soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention	Keep out of reach of children. Obtain special instructions before use. Do not handle all safety precautions have been read and understood. Avoid breathing fumes and vapors. Avoid release to the environment.
Handling	Wear protective gloves and eye protection. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Collect spillage.
Storage	Store in a well-ventilated area.

9200FR-A

FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminum metal and insoluble compounds ^{a)}	ACGIH	1 mg/m ³	Not established
	U.S.A. OSHA PEL	15 mg/m ³	Not established
	Canada AB	10 mg/m ³	Not established
	Canada BC	1 mg/m ³	Not established
	Canada ON	1 mg/m ³	Not established
	Canada QC	10 mg/m ³	Not established

Note: The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS² database and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Respirable airborne particles

Engineering Controls

Ventilation Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Ensure that glasses have side shields for lateral protection.

Skin Protection For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Section continued on the next page

9200FR-A
FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE

Respiratory Protection For over-exposures up to 10 x OEL of mist, vapors, or spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Off-white	Upper Flammability Limit	Not available
Odor	Mild	Vapor Pressure @20 °C	Not available
Odor Threshold	Not available	Vapor Density	Not available
pH	Not available	Relative Density @25 °C	1.30
Freezing/Melting Point	Not available	Solubility in Water	Slightly Soluble
Initial Boiling Point ^{a)}	≥150 °C [≥302 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{b)}	113 °C [>235 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Non Flammable	Viscosity @25 °C	>20.5 mm ² /s

a) Component with the lowest value—bisphenol-A epoxy resin (reaction product)

b) Component with the lowest value—dipentaerythritol pentaacrylate

9200FR-A
FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE
Section 10: Stability and Reactivity

Reactivity	Reacts exothermically with amines.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Avoid ignition sources, open flames, and incompatible substances.
Incompatibilities	Strong oxidizing agents, strong acids, strong bases, amines
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information
Summary of Effects and Symptoms by Routes of Exposure

Eyes	May cause redness, irritation, or pain.
Skin	May cause skin redness, irritation, dry skin, or allergic contact dermatitis.
Inhalation	May cause cough and irritation of the respiratory track.
Ingestion	May cause abdominal discomfort, nausea, and vomiting.
Chronic	Prolonged and repeated exposure may lead to skin sensitization.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
phenol, polymer with formaldehyde, glycidyl ether	4 000 mg/kg Rabbit ^{a)}	Not available	6 000 mg/kg Rabbit ^{a)}
aluminum trihydrate	Not available	Not available	Not available
ammonium polyphosphate	300 mg/kg Rat	Not available	Not available

Section continued on the next page

9200FR-A
FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE
Continued ...

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
reaction products: bisphenol-A-(epichlorohydrin) and epoxy resin ^{b)}	>15 000 mg/kg Rat ^{a)}	23 000 mg/kg Rat ^{a)}	Not available
zinc borate	>10 000 mg/kg Rat ^{a)}	10 000 mg/kg Rat ^{a)}	Not available
dipentaerythritol pentaacrylate	Not available	Not available	Not available

Note: Toxicity data from the RTECS² and ECHA were consulted. The data from supplier SDS were also consulted.

a) Supplier SDS

b) Referred to as bisphenol-A epoxy resin (reaction product)

Other Toxicological Effects

Skin corrosion/irritation	Based on component data, the mixture is a skin irritant.
Serious eye damage/irritation	Based on component data, the mixture causes serious eye irritation.
Sensitization (allergic reactions)	Based on component data, the mixture is a skin sensitizer based on animal studies.
Carcinogenicity (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Animal ingestion studies show that high doses of zinc borate cause reproductive and developmental effects.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met. There is no category 1 components, and the kinematic viscosity is >20.5 mm ² /s at 40 °C.

9200FR-A**FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

In Europe, similar epoxy resin mixtures with CAS# 28064-14-4 and 25085-99-8 have an average molecular weight of less than 700 and are generally classified as chronic category 2 aquatic pollutant due to LC50 96 h of >1 mg/L but ≤10 mg/L.

Zinc borate is a category 1 chronic aquatic pollutant with a LC50 96 h 2.4 mg/L for oncorhynchus mykiss (rainbow trout); 76 mg/L 48 h Daphnia magna (water flea).

Based on available data, aluminum trihydrate, ammonium polyphosphate and dipentaerythritol pentaacrylate are not classified as environmental hazards according to GHS criteria.

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

Chronic Ecotoxicity

Category 2

Toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Biodegradability

Not available

Bioaccumulation

Not available

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

9200FR-A

FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes under 450 L
9200FR-25ML, 9200FR-50ML

NOT REGULATED in TDG
per Special Provisions 99

FOR REFERENCE ONLY

UN number: UN3082
Shipping Name: ENVIRONMENTALLY
HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(phenol, polymer with formaldehyde,
glycidyl ether, bisphenol-A, zinc borate)

Sizes 5 L and under
NOT REGULATED in 49 CFR
per exception 171.4 (c)(2)

Class: 9
Packing Group: III
Marine Pollutant: Yes

Special Provision 99 (2): These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

Air

Refer to ICAO-IATA regulations.

Sizes 5 L and under
9200FR-25ML, 9200FR-50ML
NOT REGULATED
Not Restricted, as per Special
Provisions A197

Special Provision A197: These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Section continued on the next page

Page **12** of **15**

Revision Date: 20 March 2020 / Ver. 2.01

9200FR-A

FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE

Sea

Refer to IMDG regulations.

Sizes 5 L and under
 9200FR-25ML, 9200FR-50ML
NOT REGULATED
 per 2.10.2.7

2.10.2.7: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


USA

Other Classifications

HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		1
PHYSICAL HAZARD:		2
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

Section continued on the next page

9200FR-A**FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE****CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any listed substances in California.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by	Regulatory Department
Date of Review	04 March 2020
Supersedes	11 April 2019
Reason for Changes:	Change to emergency phone numbers.

Section continued on the next page

9200FR-A**FLAME RETARDANT STRUCTURAL EPOXY ADHESIVE****Reference**

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.