NSYS3DB3415

Spacial S3DB H300xW400xD150. IP66, IK10, RAL7035. No





Main

Range	Spacial
Product name	Spacial S3DB
Application	Terminal application
Category	Compact enclosure
Enclosure nominal height	11.81 in (300 mm)
Enclosure nominal width	15.75 in (400 mm)
Enclosure nominal depth	5.91 in (150 mm)
Door type	Solid
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Installation accessory type	Wall-mounting Horizontal or vertical position
Product destination	For equipping with terminal
Device composition	1 body 1 door 1 lock

Complementary

Body type	Gutter-shaped front rail double sheet thickness Single piece body
Number of doors	Front face 1
Door opening side	Reversible 180 °)
Lock type	3 mm double-bar lock
Accessibility for operation	Front
Removable parts	Door by hinges
Material	steel
Surface finish	Epoxy-polyester powder
Color	Gray RAL 7035)
Standards	IEC 62208
Product Certifications	BV GL DNV LR CUL UL
Net Weight	10.47 lb(US) (4.748 kg)

Environment

NEMA Degree of Protection	NEMA 4X/13	
IK degree of protection	IK10 IEC 62262	
IP degree of protection	IP66 IEC 60529	

Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480158780
Nbr. of units in pkg.	1
Package weight(Lbs)	10.47 lb(US) (4.748 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.68 in (19.5 cm)
Package 1 width	12.01 in (30.5 cm)
Package 1 Length	16.34 in (41.5 cm)
Unit Type of Package 2	PAM
Number of Units in Package 2	72
Package 2 Weight	782.64 lb(US) (355.0 kg)
Package 2 Height	81.89 in (208.0 cm)
Package 2 width	39.37 in (100.0 cm)
Package 2 Length	47.24 in (120.0 cm)

Offer Sustainability

Onor Custamasmy	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	☐ Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------