




## Dimensions: [mm]

## Recommended Land Pattern: [mm]



Scale - 1:2



Scale - 1:2

## Electrical Properties:

Properties		Test conditions	Value	Unit
Inductance	L	125 kHz / 10 mA	5.8	µH
Q-Factor	Q	125 kHz / 10 mA	220	
Rated Current DC	$I_{DC}$	$\Delta T = 40 K$	21	A
Power Capability	P	$V_{DC} = 20 V$	400	W
Saturation Current	$I_{SAT}$		30	A
DC Resistance	$R_{DC}$	$@ 20 ^\circ C$	12	mΩ
DC Resistance	$R_{DC}$	$@ 20 ^\circ C$	14	mΩ
Self Resonant Frequency	$f_{res}$		13	MHz

## Certification:

RoHS Approval	Compliant [2011/65/EU & 2015/863]
REACH Approval	Conform or declared [EC] 1907/2006]
Halogen Free	Conform [JEDEC JS709B]
Halogen Free	Conform [IEC 61249-2-21]

## General Information:

It is recommended that the temperature of the component does not exceed +105°C under case conditions

Operating Temperature	-20 up to +105 °C
Storage Conditions (in original packaging)	< 40 °C ; < 75 % RH
Moisture Sensitivity Level (MSL)	1

Test conditions of Electrical Properties: +20 °C, 33 % RH if not specified different

DESCRIPTION	WE-WPCC Wireless Power Transfer Transmitter Coil			ORDER CODE <b>760308101311</b>
	SIZE/TYP	Ø 70 x 8,5 mm	BUSINESS UNIT	
REVISION	01/001	DATE (YYMMDD)	GENERAL TOLERANCE	PROJECTION
Marking	760308101311	2020-04-09	DIN ISO 2768-1m	PERIOD
Business Unit	eSos			STATUS
				Valid


## Product Marking:

Marking	760308101311
---------	--------------

Würth Elektronik eSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Walldenburg Germany Tel. +49 (0) 70 42 945 - 0 www.we-online.com eSos@we-online.com		WE-ELEKTRONIK		
		SIZE/TYP	Ø 70 x 8,5 mm	BUSINESS UNIT
REVISION	01/001	DATE (YYMMDD)	GENERAL TOLERANCE	PROJECTION
Marking	760308101311	2020-04-09	DIN ISO 2768-1m	PERIOD
Business Unit	eSos			STATUS
				Valid

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarines, transportation signal, disaster prevention, medical, public information network etc. Würth Elektronik eSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

## Typical Inductance vs. Current Characteristics:



100


Inductance [ $\mu\text{H}$ ]

Frequency [kHz]

10

1

## Typical Inductance vs. Frequency Characteristics:



10000

1000

100

10

1

Frequency [kHz]


## Typical Inductance vs. Frequency Characteristics:

DESCRIPTION	CHECKED	REVISION	DATE (YYMMDD)	GENERAL TOLERANCE	PROJECTION
	Onite	001.001	2020-04-09	DIN ISO 2768-1m	PERIOD
WE-WPCC Wireless Power Transfer Transmitter Coil					
SIZE/TYP	Ø 70 x 8.5 mm	BUSINESS UNIT	eSos	STATUS	Valid
WURTH ELEKTRONIK	Würth Elektronik eSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Wallenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eSos@we-online.com	ORDER CODE	760308101311		




This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

## Q-Factor vs. Frequency:



## Typical Temperature Rise vs. Current Characteristics:



DESCRIPTION	CHECKED	REVISION	DATE (YYMMDD)	GENERAL TOLERANCE	PROJECTION
	Onite	001.001	2020-04-09	DIN ISO 2768-1m	PERIOD
WE-WPCC Wireless Power Transfer Transmitter Coil	SIZE/TYP				ORDER CODE
	Ø 70 x 8.5 mm	eSos			760308101311



Würth Elektronik eSos GmbH & Co. KG  
EMC & Inductive Solutions  
Max-Eyth-Str. 1  
74638 Wallenburg  
Germany  
Tel. +49 (0) 79 42 945 - 0  
www.we-online.com  
eSos@we-online.com

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. Würth Elektronik eSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

STATUS


Valid

## Classification Wave Soldering Profile

## Classification Wave Soldering Profile:

Profile Feature	Pb-Free Assembly	Sn-Pb Assembly
Preheat Temperature Min	$T_s$ min	100 °C
Preheat Temperature Typical	$T_s$ typical	120 °C
Preheat Temperature Max	$T_s$ max	130 °C
Preheat Time $t_s$ from $T_s$ min to $T_s$ max	$t_s$	70 seconds
Ramp-up Rate	$\Delta T$	150 °C max.
Peak Temperature	$T_p$	250 °C - 260 °C
Time of actual peak temperature	$t_p$	max. 10 seconds max. 5 seconds each wave
Ramp-down Rate, Min		~ 2 K/ second
Ramp-down Rate, Typical		~ 3.5 K/ second
Ramp-down Rate, Max		~ 5 K/ second
Time 25 °C to 25 °C		4 minutes

refer to EN61760-1:2006



DESCRIPTION	CHECKED	REVISION	DATE (YYMMDD)	GENERAL TOLERANCE	PROJECTION
	Orne	001.001	2020-04-09	DIN ISO 2768-1m	PERIOD
<b>WE-WPCC Wireless Power Transfer Transmitter Coil</b>	Würth Elektronik eSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Walldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eSos@we-online.com	WE-ELEKTRONIK	070 x 8.5 mm eSos	BUSINESS UNIT eSos	ORDER CODE <b>760308101311</b> STATUS Valid

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation signal, disaster prevention, medical, public information network etc. Würth Elektronik eSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

## Cautions & Warnings:

### The following conditions apply to all goods within the product series of WE-WPCC of Würth Elektronik eiSos GmbH & Co. KG:

#### General:

All recommendations according to the general technical specifications of the data sheet have to be complied with.

The usage and operation of the product within ambient conditions, which probably alloy or harm the wire isolation, has to be avoided.

If the product is potted in customer applications, the potting material might shrink during and after hardening. The product is exposed to the pressure of the potting material with the effect that the core, wire and termination is possibly damaged by this pressure and so the electrical as well as the mechanical characteristics are endangered to be affected. After the potting material is cured, the core, wire and termination of the product have to be checked if any reduced electrical or mechanical functions or destructions have occurred.

The responsibility for the applicability of customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products do also apply to customer specific products.

Cleaning agents that are used to clean the customer application might damage or change the characteristics of the component, body, pins or termination.

Direct mechanical impact to the product shall be prevented as the ferrite material of the core could flake or in the worst case it could break.

#### Product specific:

Follow all instructions mentioned in the data sheet, especially:

- The soldering profile has to be complied with according to the technical wave soldering specification, otherwise this will void the warranty.
- Reflow soldering is not applicable. Wave soldering is recommended.
- All products shall be used before the end of the period of 12 months based on the product date code, if not a 100% solderability can't be ensured.
- Violation of the technical product specifications such as exceeding the nominal rated current will void the warranty.
- Due to heavy weight of the component, strong forces and high accelerations might have the effect to damage the electrical connection or to harm the circuit board and will void the warranty.

The general and product specific cautions comply with the state of the scientific and technical knowledge and are believed to be accurate and reliable; however, no responsibility is assumed for inaccuracies or incompleteness.

DESCRIPTION	CHECKED	FEBRIOSION	DATE (YY/MM/DD)	GENERAL TOLERANCE	PROJECTION	METHOD	ORDER CODE
<b>WE-WPCC Wireless Power Transfer Transmitter Coil</b>							
	Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Walldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eisos@we-online.com	0	70 x 8.5 mm	eISOS	BUSINESS UNIT	760308101311	

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co. KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarines, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. Würth Elektronik eiSos GmbH & Co. KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

## Important Notes

### 6. Product Life Cycle

#### The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

##### 1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

##### 2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications. In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component. Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at [www.we-online.com](http://www.we-online.com).

##### 3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

##### 4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

##### 5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. Standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current availability/expectancy before or when the product for application design-in disposal is considered. The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

##### 7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development concepts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG. Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

##### 8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions Elektronik eiSos Group"; last version available at [www.we-online.com](http://www.we-online.com).

DESCRIPTION	CHECKED	REVISION	DATE (YY-MM-DD)	GENERAL TOLERANCE	PROJECTION	ORDER CODE
	Orne	001.001	2020-04-09	DIN ISO 2768-1m	PERIOD	
WE-WPCC Wireless Power Transfer Transmitter Coil	Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Walldenburg Germany Tel. +49 (0) 70 42 945 - 0 <a href="http://www.we-online.com">www.we-online.com</a> eiSos@we-online.com	0	70 x 8.5 mm	eiSos	BUSINESS UNIT	STATUS Valid
						

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co. KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarines, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. Würth Elektronik eiSos GmbH & Co. KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.