



# Photocoupler Product Data Sheet LTV-M601 Series

Spec No.: DS70-2013-0020

Effective Date: 07/06/2016

Revision: D

LITE-ON DCC

RELEASE

BNS-OD-FC001/A4

# Photocoupler LTV-M601 series

## Small Outline, 5Lead, High CMR

### 1. DESCRIPTION

The LTV-M601 series consists of a high efficient AlGaAs Light Emitting Diode and a high speed optical detector. This unique design provides maximum AC and DC circuit isolation while achieving LVTT/LVCMOS compatibility. The output of the optical detector features an open collector Schottky clamped transistor. The internal shield provides a guaranteed common mode transient immunity specification of 10 KV/us at 3.3/5V operation. The Optocoupler operational parameters are guaranteed over the temperature range from -40°C ~ +85°C.

#### 1.1 Features

- 3.3V / 5V Dual Supply Voltages
- Low power consumption
- High speed – 15MBd typical
- Low input current capability: 3mA
- 10KV/μs minimum Common Mode Rejection (CMR) at  $V_{CM} = 1000V$
- Guaranteed AC and DC performance over temperature -40°C ~ +85°C.
- LVTT/LVCMOS Compatible.
- Strobable output.
- Safety approval

UL/ cUL 1577, 3750 Vrms/1 min


VDE DIN EN60747-5-5,  $V_{IORM} = 567$  Vpeak

#### 1.2 Applications

- Isolation in line receivers
- Ground loop elimination
- Feedback Element in Switching Mode Power Supplier
- High Speed Logic Ground Isolation – TTL/TTL, TTL/CMOS, TTL/LSTTL
- Pulse transformer replacement
- Power transistor isolation in motor drives
- Interface between Microprocessor system, computer and their peripheral

#### Functional Diagram

Pin No. and Internal connection diagram



#### Truth Table (Positive Logic)


LED	OUT
ON	L
OFF	H

A 0.1μF bypass Capacitor must be connected between Pin4 and Pin6

# Photocoupler LTV-M601 series

## 2. PACKAGE DIMENSIONS

### 2.1 LTV-M601 series



#### Notes :


1. The first digit is year date code, second and third digit is work week
2. Factory identification mark (W :China-CZ)  
Dimensions are all in Millimeters.
3. "4"or"V"for VDE option.

\* Dimensions are in Millimeters and (Inches).


# Photocoupler LTV-M601 series

## 3. TAPING DIMENSIONS

### 3.1 LTV-M601



### 3.2 LTV-M601-TP



Description	Symbol	Dimension in mm (inch)
Tape wide	W	12 ± 0.3 (.472)
Pitch of sprocket holes	P <sub>0</sub>	4 ± 0.1 (.157)
Distance of compartment	F	5.5 ± 0.1 (.217)
Distance of compartment to compartment	P <sub>2</sub>	2 ± 0.1 (.079)
	P <sub>1</sub>	8 ± 0.1 (.315)

### 3.3 Quantities Per Reel

Package Type	LTV-M601 series
Quantities (pcs)	3000

# Photocoupler LTV-M601 series

## 4. RATING AND CHARACTERISTICS

### 4.1 Absolute Maximum Ratings at Ta=25°C \*

	Parameter	Symbol	Rating	Unit	Note
Input	Average Forward Input Current	I <sub>F</sub>	20	mA	2
	Reverse Input Voltage	V <sub>R</sub>	5	V	
	Power Dissipation	P <sub>I</sub>	40	mW	
Output	Output Collector Current	I <sub>O</sub>	50	mA	
	Output Collector Voltage	V <sub>O</sub>	7	V	
	Output Collector Power Dissipation	P <sub>O</sub>	85	mW	
	Isolation Voltage	V <sub>iso</sub>	3750	V <sub>rms</sub>	
	Supply Voltage	V <sub>CC</sub>	7	V	
	Operating Temperature	T <sub>opr</sub>	-40 ~ +85	°C	
	Storage Temperature	T <sub>stg</sub>	-40 ~ +125	°C	
	Lead Solder Temperature **	T <sub>sol</sub>	260	°C	

\*Ambient temperature = 25°C, unless otherwise specified. Stresses exceeding the absolute maximum ratings can cause permanent damage to the device. Exposure to absolute maximum ratings for long periods of time can adversely affect reliability.

\*\*260°C for 10 seconds. Refer to Lead Free Reflow Profile.

### 4.2 Recommended Operating Conditions

Parameter	Symbol	Min	Max	Unit
Operating Temperature	T <sub>A</sub>	-40	85	°C
Supply Voltage	V <sub>CC</sub>	2.7	3.6	V
		4.5	5.5	
Low Level Input Current	I <sub>FL</sub>	0	250	µA
High Level Input Current	I <sub>FH</sub>	5	15	mA
Output Pull-up Resistor	R <sub>L</sub>	330	4k	Ω
Fan Out (at R <sub>L</sub> =1kΩ per channel)	N	—	5	TTL Loads

Photocoupler  
**LTV-M601 series**

## 4.3 ELECTRICAL OPTICAL CHARACTERISTICS

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition	Fig.	Note
<b>Input</b>								
Input Forward Voltage	V <sub>F</sub>	—	1.38	1.80	V	I <sub>F</sub> =10mA, T <sub>A</sub> =25°C	7	
Input Forward Voltage Temperature Coefficient	ΔV <sub>F</sub> /ΔT	—	-1.6	—	mV/°C	I <sub>F</sub> =10mA		
Input Reverse Voltage	BV <sub>R</sub>	5.0	—	—	V	I <sub>R</sub> = 10μA		
Input Threshold Current	I <sub>TH</sub>	—	1.5	5	mA	V <sub>CC</sub> =3.3V, V <sub>O</sub> = 0.6V I <sub>OL</sub> (sinking) = 13mA	4	
Input Capacitance	C <sub>IN</sub>	—	34	—	pF	V <sub>F</sub> =0; f=1MHz		
<b>Detector</b>								
Logic low output voltage	V <sub>OL</sub>	—	0.3	0.6	V	V <sub>CC</sub> = 3.3V, I <sub>F</sub> = 5mA, I <sub>OL</sub> (sinking) = 13mA	5	
Logic high output current	I <sub>OH</sub>	—	5	100	μA	V <sub>CC</sub> = 3.3V, V <sub>O</sub> = 3.3V, I <sub>F</sub> = 250μA	3	
Logic low supply current	I <sub>CCL</sub>	—	5.8	10	mA	V <sub>CC</sub> = 3.3V, I <sub>F</sub> = 10mA		1
Logic high supply current	I <sub>CCH</sub>	—	3.8	7	mA	V <sub>CC</sub> = 3.3V, I <sub>F</sub> = 0mA		1

Specified over recommended temperature (T<sub>A</sub> = -40°C to +85°C, 2.7V ≤ V<sub>CC</sub> ≤ 3.6V), I<sub>F</sub> = 7.5mA unless otherwise specified. All typicals at T<sub>A</sub> = 25°C, V<sub>CC</sub> = 3.3V.

Photocoupler  
**LTV-M601 series**

## 4.4 ELECTRICAL OPTICAL CHARACTERISTIC

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition	Fig.	Note
<b>Input</b>								
Input Forward Voltage	V <sub>F</sub>	—	1.38	1.80	V	I <sub>F</sub> =10mA, T <sub>A</sub> =25°C	7	
Input Forward Voltage Temperature Coefficient	ΔV <sub>F</sub> /ΔT	—	-1.6	—	mV/°C	I <sub>F</sub> =10mA		
Input Reverse Voltage	BV <sub>R</sub>	5.0	—	—	V	I <sub>R</sub> = 10μA		
Input Threshold Current	I <sub>TH</sub>	—	1.57	5	mA	V <sub>CC</sub> = 5.5V, V <sub>O</sub> =0.6V I <sub>OL</sub> ≥ 13mA	4	
Input Capacitance	C <sub>IN</sub>	—	34	—	pF	V <sub>F</sub> =0; f=1MHz		
<b>Detector</b>								
Logic low output voltage	V <sub>OL</sub>	—	0.4	0.6	V	V <sub>CC</sub> = 5.5V, I <sub>F</sub> = 5mA, I <sub>OL</sub> (sinking) = 13mA	5	
Logic high output current	I <sub>OH</sub>	—	3	100	μA	V <sub>CC</sub> = 5.5V, V <sub>O</sub> = 5.5V, I <sub>F</sub> = 250μA	3	
Logic low supply current	I <sub>CCL</sub>	—	8	13	mA	V <sub>CC</sub> = 5.5V, I <sub>F</sub> = 10mA		1
Logic high supply current	I <sub>CCH</sub>	—	6	10	mA	V <sub>CC</sub> = 5.5V, I <sub>F</sub> = 0mA		1

Specified over recommended temperature (T<sub>A</sub> = -40°C to +85°C, 4.5V ≤ V<sub>CC</sub> ≤ 5.5V), I<sub>F</sub> = 7.5mA unless otherwise specified. All typicals at T<sub>A</sub> = 25°C, V<sub>CC</sub> = 5.0V.

## Photocoupler LTV-M601 series

### 5. SWITCHING SPECIFICATION

Parameter	Symb	Min.	Typ.	Max.	Unit	Test Condition	Fig.	Note
Propagation Delay Time to High Output Level	$t_{PLH}$	—	60	90	ns	$R_L = 350\Omega, C_L = 15pF$	1,9	3
Propagation Delay Time to Low Output Level	$t_{PHL}$	—	25	75			1,9	4
Pulse Width Distortion	$ t_{PLH} - t_{PHL} $	—	35	45			10	—
Propagation Delay Skew	$t_{PSK}$	—	—	40			—	—
Output Rise Time (10 to 90%)	$t_r$	—	27	—			—	—
Output Fall Time (90 to 10%)	$t_f$	—	7	—			—	—

Specified over recommended temperature ( $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ ,  $2.7V \leq V_{CC} \leq 3.6V$ ),  $I_F = 7.5\text{mA}$  unless otherwise specified. All typicals at  $T_A = 25^\circ\text{C}$ ,  $V_{CC} = 3.3\text{V}$ .

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition	Not	Fig.
Propagation Delay Time to High Output Level	$t_{PLH}$	—	45	75	ns	$T_A = 25^\circ\text{C}$ $R_L = 350\Omega, C_L = 15pF$	1,9	3
		—	—	100				
Propagation Delay Time to Low Output Level	$t_{PHL}$	—	25	75	ns	$T_A = 25^\circ\text{C}$ $R_L = 350\Omega, C_L = 15pF$	1,9	4
		—	—	100				
Pulse Width Distortion	$ t_{PLH} - t_{PHL} $	—	10	35		$R_L = 350\Omega, C_L = 15pF$	10	—
Propagation Delay Skew	$t_{PSK}$	—	—	40			—	—
Output Rise Time (10 to 90%)	$t_r$	—	21	—			—	—
Output Fall Time (90 to 10%)	$t_f$	—	7	—			—	—

Specified over recommended temperature ( $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ ,  $4.5V \leq V_{CC} \leq 5.5V$ ),  $I_F = 7.5\text{mA}$  unless otherwise specified. All typicals at  $T_A = 25^\circ\text{C}$ ,  $V_{CC} = 5.0\text{V}$ .

Photocoupler  
**LTV-M601 series**

Parameter	Test Condition	Sym.	Min.	Typ.	Max.	Units	Fig.	Note
Common Mode Transient Immunity at High Output Level	$V_{CC} = 3.3V$ $V_{CM} = 1000V$ $R_L = 350\Omega$ $I_F = 0mA$ $T_A = 25^\circ C$	$ CM_H $	10	15		KV/ $\mu$ s	2	5
	$V_{CC} = 5V$ $V_{CM} = 1000V$ $R_L = 350\Omega$ $I_F = 0mA$ $T_A = 25^\circ C$							
Common Mode Transient Immunity at Low Output Level	$V_{CC} = 3.3V$ $V_{CM} = 1000V$ $R_L = 350\Omega$ $I_F=10.0mA$ $T_A = 25^\circ C$	$ CM_L $	10	15		KV/ $\mu$ s	2	6
	$V_{CC} = 5V$ $V_{CM} = 1000V$ $R_L = 350\Omega$ $I_F=10.0mA$ $T_A = 25^\circ C$							

Photocoupler  
**LTV-M601 series**

## 6. ISOLATION CHARACTERISTIC

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition	Note
Input-Output Insulation Leakage Current	I <sub>I-O</sub>	—	—	1.0	µA	45% RH, t = 5s, V <sub>I-O</sub> = 3kV DC, T <sub>A</sub> = 25°C	7
Withstand Insulation Test Voltage	V <sub>ISO</sub>	3750	—	—	V <sub>RMS</sub>	RH ≤ 50%, t = 1min, T <sub>A</sub> = 25°C	7, 8
Input-Output Resistance	R <sub>I-O</sub>	—	10 <sup>12</sup>	—	Ω	V <sub>I-O</sub> = 500V DC	7
Input-Output Capacitance	C <sub>I-O</sub>	—	1.0	—	p	f = 1MHz, T <sub>A</sub> = 25°C	7

Specified over recommended temperature (T<sub>A</sub> = -40°C to +85°C) unless otherwise specified. Typical values applies to T<sub>A</sub> = 25°C

### Note

1. A 0.1µF or bigger bypass capacitor for V<sub>CC</sub> is needed as shown in Fig.1
2. Peaking driving circuit may be used to speed up the LED. The peak drive current of LED may go up to 50mA and maximum pulse width 50ns, as long as average current doesn't exceed 20mA.
3. t<sub>PLH</sub> (propagation delay) is measured from the 3.75 mA point on the falling edge of the input pulse to the 1.5 V point on the rising edge of the output pulse.
4. t<sub>PHL</sub> (propagation delay) is measured from the 3.75 mA point on the rising edge of the input pulse to the 1.5 V point on the falling edge of the output pulse.
5. CM<sub>H</sub> is the maximum tolerable rate of rise of the common mode voltage to assure that the output will remain in a high logic state (i.e., VO > 2.0 V).
6. CM<sub>L</sub> is the maximum tolerable rate of fall of the common mode voltage to assure that the output will remain in a low logic state (i.e., VO < 0.8 V).
7. Device is considered a two-terminal device: pins 1, 3 shorted together, and pins 4, 5, 6 shorted together.
8. In accordance with UL1577, each optocoupler is proof tested by applying an insulation test voltage 4500 Vrms for one second (leakage current less than 10 uA). This test is performed before the 100% production test for partial discharge

## Photocoupler LTV-M601 series

### 7. SWITCHING TIME TEST CIRCUIT




Figure 1: Test Circuit for  $t_{PHL}$  and  $t_{PLH}$




Figure 2: Test Circuit for Common Mode Transient Immunity

## Photocoupler LTV-M601 series

### 8. TYPICAL PERFORMANCE CURVES





Figure 3: Typical high level output current vs. temperature.





Figure 4: Typical Input Diode Threshold Current vs. Ambient Temperature





Figure 5: Typical Low Level Output Voltage vs. Ambient Temperature

## Photocoupler LTV-M601 series





Figure 6: Typical Low Level Output Current vs. Ambient Temperature




Figure 7: Typical Input Diode Forward Characteristics




Figure 8: Typical Input Diode Forward Voltage vs. Ambient Temperature

## Photocoupler LTV-M601 series





Figure 9: Typical Propagation Delay vs. Ambient Temperature





Figure 10: Typical Pulse Width Distortion vs. Ambient


## Photocoupler LTV-M601 series

### 9. TEMPERATURE PROFILE OF SOLDERING

#### 9.1 IR Reflow soldering (JEDEC-STD-020C compliant)

One time soldering reflow is recommended within the condition of temperature and time profile shown below. Do not solder more than three times.

Profile item	Conditions
Preheat	
- Temperature Min ( $T_{Smin}$ )	150°C
- Temperature Max ( $T_{Smax}$ )	200°C
- Time (min to max) ( $t_s$ )	90±30 sec
Soldering zone	
- Temperature ( $T_L$ )	217°C
- Time ( $t_L$ )	60 ~ 100sec
Peak Temperature ( $T_P$ )	260°C
Ramp-up rate	3°C / sec max.
Ramp-down rate	3~6°C / sec



## Photocoupler LTV-M601 series

### 9.2 Wave soldering (JEDEC22A111 compliant)


One time soldering is recommended within the condition of temperature.

Temperature:  $260+0/-5^{\circ}\text{C}$

Time: 10 sec.

Preheat temperature: 25 to  $140^{\circ}\text{C}$

Preheat time: 30 to 80 sec.



### 9.3 Hand soldering by soldering iron

Allow single lead soldering in every single process. One time soldering is recommended.

Temperature:  $380+0/-5^{\circ}\text{C}$

Time: 3 sec max.

## Photocoupler LTV-M601 series

### 10. NAMING RULE

Part Number Options
LTV-M601-TP
LTV-M601
LTVM601TP-V
LTVM601-V

Definition of Suffix	Remark
"M601"	LiteOn model name
" no suffix "	Pin 1 location at upper right of the tape
"TP"	Pin 1 location at lower left of the tape
"V"	VDE approved option

### 11. NOTES

LiteOn is continually improving the quality, reliability, function or design and LiteOn reserves the right to make changes without further notices.

The products shown in this publication are designed for the general use in electronic applications such as office automation equipment, communications devices, audio/visual equipment, electrical application and instrumentation.

For equipment/devices where high reliability or safety is required, such as space applications, nuclear power control equipment, medical equipment, etc, please contact our sales representatives.

When requiring a device for any "specific" application, please contact our sales in advice.

If there are any questions about the contents of this publication, please contact us at your convenience.

The contents described herein are subject to change without prior notice.

Immerge unit's body in solder paste is not recommended.