



Click [here](#) for the 3D model.

Dimensions

| | |
|----|--------------------|
| L | 12.7mm MAX |
| W | 12.7mm MAX |
| T | 3.81mm MAX |
| S | 10.16mm +/-0.76mm |
| LL | 3.175mm MIN |
| F | 0.635mm +/-0.051mm |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 1 |

General Information

| | |
|-------------------------|--------------------------------------|
| Series | TCR Indust COG HT260C |
| Style | Radial |
| Description | Commercial, High Temperature |
| Features | Commercial |
| RoHS | With Exemptions |
| REACH | SVHC (Pb - CAS 7439-92-1) |
| SCIP Number | a5a9e204-6d6a-49c3-acf7-37d0b4e9df91 |
| Termination | Gold |
| Failure Rate | N/A |
| Testing and Reliability | Standard |
| AEC-Q200 | No |

Specifications

| | |
|---------------------------------|---------------------|
| Capacitance | 0.1 uF |
| Capacitance Tolerance | 10% |
| Voltage DC | 50 VDC |
| Dielectric Withstanding Voltage | 125 VDC |
| Temperature Range | -55/+260°C |
| Temperature Coefficient | COG |
| Dissipation Factor | 0.15% 1 kHz 1.0Vrms |
| Insulation Resistance | 10 GOhms |