## Data sheet | Item number: 706-100/340-300

Connection cable; 40-pole; Pluggable connector per DIN 41651; open-

ended; Length: 3 m; Conductor cross-section: 0.14 mm<sup>2</sup>

www.wago.com/706-100/340-300





Color coding acc. to DIN VDE 47100		40 poles flat connector
		Pin number
White		1
Brown		2
Green		3
Yellow		4
Grey		5
Pink		6
Blue		7
Red		8
Black		9
Violet		10
Grey-Pink		11
Red-Blue		12
White-Green		13
Brown-Green		14
White-Yellow		15
Yellow-Brown		16
White-Grey		17
Grey-Brown		18
White-Pink		19
Pink-Brown		20
White-Blue		21
Brown-Blue		22
White-Red		23
Brown-Red		24
White-Black		25
Brown-Black		26
Grey-Green		27
Yellow-Grey		28
Pink-Green		29
Yellow-Pink		30
Green-Blue		31
Yellow-Blue		32
Green-Red		33
Yellow-Red		34
Green-Black		35
Yellow-Black		36
Grey-Blue		37
Pink-Blue		38
Grey-Red		39
Pink-Red		40
T IIIN-NGU		

# Data Notes

Note

When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$ 

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

### Data sheet | Item number: 706-100/340-300

www.wago.com/706-100/340-300



#### Electrical data

Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	1 A

#### Connection data

Cable type	LiYY
Color code	per DIN VDE 47100

## **Connection 1**

Connector	Pluggable connector per DIN 41651; female connector
Pole number 1	40
Connection type 1	System
Wire cross-section	0.14 mm²
Connection type	Pluggable Connector per DIN 41651

#### Connection 2

Connector 2	open-ended
Connection type 2	open-ended

# Physical data

Cable length	3 m
--------------	-----

### **Material Data**

Weight	618 g	
--------	-------	--

## **Environmental requirements**

pient temperature (operation) -20	20 +50 °C
nerit temperature (operation)	.000 0

### Commercial data

ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	bag
Country of origin	FR
GTIN	4055143976374

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$ 

WAGO GmbH & Co. KG

Do you have any questions about our products?

Hansastr. 27

We are always happy to take your call at +49 (57)

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com We are always happy to take your call at +49 (571) 887-44222.

#### Data sheet | Item number: 706-100/340-300

www.wago.com/706-100/340-300



Customs tariff number 85444290900

**Environmental Product Compliance** 

RoHS Compliance Status Compliant, No Exemption

**Downloads** 

**Environmental Product Compliance** 

Compliance Search

Environmental Product Compliance 706-100/340-300

URL

Download

Connection cable; 40-pole; Pluggable connector per DIN 41651; open-ended; Length: 3 m; Conductor cross-section: 0.14 mm<sup>2</sup>

**Installation Notes** 

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.