Product data sheet Characteristics

NSYTBP292412HT PC box IP66 IK08 RAL7035 Int.H275W225D120 Ext.H291W241D128 Transp.cover H60





Main	
Range	Thalassa
Product name	Thalassa TBP
Device Application	Multi-purpose
Category	Industrial box
Height	11.46 in (291 mm)
Width	9.49 in (241 mm)
Depth	5.04 in (128 mm)
Internal height	10.83 in (275 mm)
Internal width	8.86 in (225 mm)
Internal depth	4.72 in (120 mm)
Enclosure mounting	Wall mounted
Device composition	1 body 1 cover 4 cover screw
Body type	One piece moulded
Type of front cover	High transparent cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

Complementary

Material	polycarbonate	
Color	Gray RAL 7035) Transparent	
Standards	IEC 62208 UL 508 A	
Product Certifications	TÜV UL	
Electrical Insulation Class	Class II	
Mounting location	Outdoor	
Net Weight	2.65 lb(US) (1.2 kg)	

Environment

IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK08 IEC 62262
Fire resistance	1760 °F (960 °C)
Ambient Air Temperature for Storage	5140 °F (-1560 °C)
Operating temperature	-13176 °F (-2580 °C)

Ordering and shipping details

Category	80033-ENCLOSURE SYSTEMS POLYESTER	
Discount Schedule	ES1	
GTIN	3606480165894	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.68 lb(US) (1.214 kg)	



Returnability	No
Country of origin	HU

Packing Units

r doking onits	
Unit Type of Package 1	PCE
Package 1 Height	5.91 in (15.0 cm)
Package 1 width	9.84 in (25.0 cm)
Package 1 Length	12.20 in (31.0 cm)
Unit Type of Package 2	PAM
Number of Units in Package 2	150
Package 2 Weight	488.32 lb(US) (221.5 kg)
Package 2 Height	86.61 in (220.0 cm)
Package 2 width	39.37 in (100.0 cm)
Package 2 Length	47.24 in (120.0 cm)
Unit Type of Package 3	CAR
Number of Units in Package 3	6
Package 3 Weight	18.19 lb(US) (8.25 kg)
Package 3 Height	15.75 in (40.0 cm)
Package 3 width	15.75 in (40.0 cm)
Package 3 Length	23.62 in (60.0 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) CEU RoHS
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫ Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty

18 months