XZCE13M125M

Adaptor, metal, tapped hole Pg 13.5, for male connector, M12, 5 wire



Main	
Accessory / separate part designation	5-wire connector adaptor
Accessory / separate part category	Cabling accessories
Accessory / Separate Part Type	Connector adaptor
Cable composition	4 x 0.34 mm² + 1 x 0.5 mm²
Thread type	Pg 13.5
Line Rated Current	4 A

Complementary

Cable length	3.94 in (100 mm)	
Total number of wires	5	
Electrical connection	1 male connector M12 5 straight	
Cable connector fixing	Screw-on	
Body Material	Metal	
Insulation resistance	> 1000000000 Ohm	
Maximum resistance across terminals	5000 mOhm	
[Ue] rated operational voltage	30 V AC 36 V DC	
Net Weight	0.06 lb(US) (0.025 kg)	

Environment

2. Tritoriment	
IP Degree of Protection	IP67
Ambient Air Temperature for Operation	-13176 °F (-2580 °C)

Ordering and shipping details

Category	22483-MACHINE CABLES
Discount Schedule	DS3
GTIN	3389110835519
Nbr. of units in pkg.	1
Package weight(Lbs)	0.92 oz (26.0 g)
Returnability	No
Country of origin	CZ

Packing Units


Unit Type of Package 1	PCE	
Package 1 Height	1.14 in (2.9 cm)	
Package 1 width	1.97 in (5 cm)	
Package 1 Length	5.67 in (14.4 cm)	
Unit Type of Package 2	S02	
Number of Units in Package 2	100	
Package 2 Weight	6.62 lb(US) (3.003 kg)	
Package 2 Height	5.91 in (15 cm)	

Package 2 width	11.81 in (30 cm)	
Package 2 Length	15.75 in (40 cm)	
Offer Sustainability		
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
Contractual warranty		
Warranty	18 months	

Product data sheet Dimensions Drawings

XZCE13M125M


Dimensions



Product data sheet Connections and Schema

XZCE13M125M

Connections and Schemes



BN: Brown BK: Black BU: Blue

Y/G : Yellow / Green WH : White