

POS.		Α	В	С	D	E	F	G
	15	1.213	0.984	0.666	0.756	0.329	0.606	0.496
	26	1.543	1.312	0.994	1.091	0.329	0.954	0.496
	44	2.087	1.852	1.534	1.618	0.329	1.498	0.496
	62	2.732	2.500	2.181	2.256	0.329	2.147	0.496
	78	2.083	2.406	2.079	2.169	0.445	2.043	0.606

.240

**SPECIFICATIONS:** 

**MATERIALS:** 

SHELL: STEEL, TIN PLATED

**INSULATOR: UL 94V-0 RATED BLACK PBT** 

+30% FIBER-GLASS OR NYLON-66

**ELECTRICALS:** 

**CURRENT RATING: 2 AMPS** 

**CONTACT RESISTANCE: 15 mOHMS MAX INSULTOR RESISTANCE: 1000 MOHMS MIN** 

**VOLTAGE: 500V AC FOR 1 MINUTE** TEMPERATURE: -50°C TO +100°C

	180-XXX-172-XX0
SERIES —	
POSITIONS —	
015	
026 044	
0 <del>44</del> 062	
07 <u>8</u>	
GENDER_	———————————————————————————————————————
1 = MALE 2 = FEMALE	
TERMINATION ——— 7 = CRIMP/POKE	
SHELL PLATING —	
2 = TIN	
HARDWARE OPTIONS	s ————
00 = NO HARDWARE	ILIT DOADD OIDE
01 = .098 4-40 CLINCH N 02 = .250 4-40 CLINCH N	IUT BOARD SIDE
03 = .250 4-40 CLINCH N	
91 = .225 4-40 SPACER/E	
PLATING OPTIONS -	
0 = NO CONTACTS	

	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NOrCOMP AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWN:	1	DATE:		
<b>M</b>		PAM JENKIN	IS	8-12-98	3	
		CHECKED:		DATE:		
		SCALE:	SHEE	ET OF	REV	
NI	vk( 'omn				3	
INC		DWG NO.				
		180-XXX-172-XX0				



