

| Preliminary Specificat             |                               | Written by <u>K. Riku</u><br>Chacked by T. Kuriyan     |  |  |
|------------------------------------|-------------------------------|--|--|--|
| Preliminary SPEC No<br>Part Number | . : <u>NMM04-</u><br>: MXFR01 | Checked by <u>T. Kuriyan</u><br>Date <u>13/Apr./20</u> |  |  |
| SPECIFICATION                      | . MIXENOT                     |  | A: 14/Jun./'10 LH, B: 08/Oct./'10 LH, C: 21/Oct./' |  |
| )                                  |                               | Revised  |  |  |
| 1. MECHANICAL                      |                               |  |  |  |
|                                    | 1:                            | 3.0+/-0.5  | 1.5  |  |
| Dia.8.9+/-0.3                      | *3                            | -  | <u>*2</u> *1                                       |  |
|                                    |                               |  |  |  |
| 22.8                               |                               |  | ╎┟┄┈╴╢╾┈╌┥┲╌╍╌╸╸╸╸╸╸╸╸╸╸╸                          |  |
|                                    |                               |  |  |  |
|                                    |                               |  |  |  |
| HEX 8.0                            |                               |  |  |  |
| <                                  | ⇒ _                           |  | L  |  |
|                                    | *1 0                          |  | angle plug connector Scale: Free                   |  |
|                                    | *1. Connect<br>*2. Cable      | or: JSC right  | angle plug connector Scale: Free Unit: mm          |  |
|                                    |                               | or, SMA stra   | ight Jack connector                                |  |
|                                    |                               | .,   |  |  |
| Tolerances Unless Ot               | herwise Specified ±           | 0.2  |  |  |
| Enclosed attachment:               | Mounting Nut 1p               | DC,  |  |  |
|                                    | Lock Washer 1                 | lpc  |  |  |
| Plating: Contact                   |                               |  |  |  |
| Housing                            | Mounting Nut, Lock            | ( wasner   |  |  |
|                                    |                               | 10   | 0 +/- 3  |  |
| •B >C<br>2. CABLE :                |                               | 10   |  |  |
|                                    | Item                          |  | Specification                                      |  |
| 2.1 Voltage                        | Rating                        |  | 30V r.m.s. maximum                                 |  |
| 2.2 Nomina                         | al Frequency Range            |  | DC to 12 GHz                                       |  |
| 2.3 Nomina                         | al Impedance                  |  | 50Ω  |  |
| 2.4 Tempe                          | 2.4 Temperature Rating        |  | -40°C to +85°C                                     |  |
| 2.5 Used C                         | able                          |  | 0.4D Single shield PFA cable                       |  |
|                                    | 14                            | 1.1-14   |  |  |
| lanar                              | Item                          | Unit   | Construction                                       |  |
| Inner<br>conductor                 | Material<br>No. and Dia.      | -<br>(No./mm)  | Silver plated copper wire<br>7/0.05                |  |
| conductor                          | Total Dia.                    | (mm)   | 0.15   |  |
| Insulator                          | Material                      | _  | PFA  |  |
|                                    | Total Dia.                    | (mm)   | 0.43   |  |
| Outer                              | Material                      | -  | Silver plated copper wire                          |  |
| conductor                          | Dia. of wire                  | (mm)   | 0.05   |  |
| Sheath                             | Material                      | -  | PFA(White)   |  |
|                                    | Nominal                       | (mm)   | 0.07   |  |
|                                    | thickness.                    |  |  |  |
| Overall Dia.                       |                               | (mm)   | 0.81   |  |
| Minimum Be                         | Minimum Bending Radius        |  | 3.3  |  |
| Nominal                            | dB/m at 1                     | GHz  | 2.99   |  |
| Insertion los                      |                               |  | 4.32   |  |
|                                    | dB/m at 3                     |  | 5.33   |  |
|                                    | dB/m at 4                     |  | 6.26   |  |
|                                    | dB/m at 6GHz                  |  | 7 00   |  |
|                                    | dB/m at 6<br>dB/m at 9        |  | 7.83   |  |

12.22

dB/m at 12GHz



| Preliminary Specification c | of COAXIAL CONNECTOR | _ Written by                     | <u>K. Riku</u>      |
|-----------------------------|----------------------|----------------------------------|---------------------|
| Preliminary SPEC No.        | : NMM04-PJ0011C      | Checked by                       | <u>T. Kuriyama</u>  |
| Part Number                 | : MXFR01JA1000       | _ Date                           | <u>13/Apr./2010</u> |
| SPECIFICATION               | Revised A: 14/J      | un./'10 LH, B: 08/Oct./'10 LH, C | C: 21/Oct./'10 LH   |

3. NOTE

Use tool part# M19201.

The connector to be engaged and disengaged should be inserted or pulled out to the vertical direction.

## 4. ACAUTION

## Limitation of Applications

Please do not use our products for the applications listed below which require specially high reliability for the prevention of defects which may directly or indirectly cause damage to the third party's life, body or property.

- (1) Aircraft equipment
- (2) Aerospace equipment
- (3) Undersea equipment
- (4) Power plant control equipment
- (5) Medical equipment
- (6) Transportation equipment (vehicles, trains, ships, etc.)
- (7) Traffic signal equipment
- (8) Disaster prevention / crime prevention equipment
- (9) Data-processing equipment
- (10) Application of similar complexity and/or reliability requirements to the applications listed in the above.