




UNCONTROLLED DOCUMENT













LEAD FREE REFLOW PROFILE



TOTAL TIME ABOVE 220°C IS 6D SECONDS MAX.

RECOMMENDED SOLDER PAD LAYOUT



PART NUMBER

SML-LXF0805SGD-TR

REV. E.C.N. NUMBER AND REVISION COMMENTS DATE E.C.N. #11148. 2.14,05

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C $I_f = 20 \text{mA}$

DADAMETED	MIN	TVD	MAV	HMITC	TECT COND
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		565		nm	
FORWARD VOLTAGE		2.2	2.6	V_f	
REVERSE VOLTAGE	5.0			٧r	Ir=100µA
axial intensity		12		mcd	$I_f = 20 \text{mA}$
VIEWING ANGLE		120		2x theta	
EMITTED COLOR:	GREEN				
EPOXY LENS FINISH:	GREEN	DIFFUSED			

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	100	mW
DERATE FROM 25°C	- 1.2	mW/°C
OPERATING TEMP.	- 30 TO +85	•c
STORAGE TEMP.	- 40 TO +85	.c

* t<10µS

NOTES:

1. THE POLARITY MARK IS ORIENTED TOWARDS THE TAPE SPROCKET HOLE.

CAUTION: MOISTURE SENSITIVE DEVICE PER JEDEC LEVEL 4 STANDARDS



REV.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X,X=±0.5 (±0.020), X,XX=±0.25 (±0.010), X,XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (0.002), LEAD LENGTH=±0.75 (±0.030). MN= +0EC.MAL PRECISION ARE: X=±1 (±0.030). MN= +0.000

REV. PART NUMBER SML-LXF0805SGD-TR

2.0mm x 1.25mm SURFACE MOUNT LED, 565nm GREEN LED. SUPER GREEN DIFFUSED LENS. TAPE AND REEL.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LIMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUNICX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847,359,2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

CHECKED BY: DRAWN BY: APPROVED BY: DATE: 4.22.03 1 OF 1 PAGE: SCALE: N/A GB