Product data sheet Characteristics

XS1M18PC410D

inductive sensor XS1 M18, L60mm, brass, Sn5mm, 12..24VDC, M12





Main

Range of Product	Telemecanique Inductive proximity sensors XS
Series name	General purpose
Sensor Type	Inductive proximity sensor
Sensor name	XS1
Sensor design	Cylindrical M18
Size	72 mm
Body type	Fixed
Detector flush mounting acceptance	Flush mountable
Material	Metal
Type of output signal	Discrete
Wiring Technique	4-wire
[Sn] nominal sensing distance	0.20 in (5 mm)
Discrete output function	1 NO + 1 NC
Output circuit type	DC
Discrete output type	PNP
Electrical connection	Male connector M12, 4 pins
[Us] rated supply voltage	1224 V DC reverse polarity protection
Switching capacity in mA	<= 200 mA overload and short-circuit protection
IP degree of protection	IP69K conforming to DIN 40050 IP65 conforming to IEC 60529 IP67

Complementary

Complementary		
Thread type	M18 x 1	
Detection face	Frontal	
Front material	PPS	
Enclosure Material	Nickel Plated Brass	
Operating zone	0.000.16 in (04 mm)	
Differential travel	115% of Sr	
Status LED	Output state 1 LED yellow)	
Supply voltage limits	936 V DC	
Switching frequency	<= 2000 Hz	
Maximum voltage drop	<2 V closed)	
Current consumption	010 mA no-load	
Maximum delay first up	5 ms	
Maximum delay response	0.15 ms	
Maximum delay recovery	0.35 ms	
Marking	CE	
Threaded length	2.01 in (51 mm)	
Length	2.83 in (72 mm)	
Net Weight	0.09 lb(US) (0.04 kg)	

Environment

Product Certifications	CSA UL
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)
Vibration resistance	25 gn +/- 2 mm 1055 Hz)IEC 60068-2-6
Shock resistance	50 gn 11 ms IEC 60068-2-27

Ordering and shipping details

Category	22486-SENSORS, PROXIMITY	
Discount Schedule	DS2	
GTIN	3389110955880	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.29 oz (65.0 g)	
Returnability	No	
Country of origin	FR	

Packing Units

. doming office	
Unit Type of Package 1	PCE
Package 1 Height	0.79 in (2 cm)
Package 1 width	3.94 in (10 cm)
Package 1 Length	4.72 in (12 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	22
Package 2 Weight	3.54 lb(US) (1.604 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months