9013GHG5S2J65

Square D Pumptrol, pressure switch 480 VAC 10 A g special





iviain	
Device short name	G
Enclosure type	Standard environment enclosure indoor
Product Specific Application	Control electrically driven water pumps and air compressors

Square D Pumptrol

Standard

Complementary 80...250 psi (551.58...1723.69 kPa) Adjustable range on rising pressure 24...45 psi (165.47...310.26 kPa) Approximate adjustable differential Depth 3.68 in (93.47 mm) Electrical connection Screw clamp terminal By brackets Fixing Mode 0.25 inch NPSF internal Fluid connection type 5.72 in (145.29 mm) Height Material Zinc plated steel flange Materials in contact with fluid Nitrile (Buna-N) diaphragm Maximum pressure 300 psig Maximum Horse Power Rating 2 Hp 115 V AC, 1 phase 3 Hp 115 V AC, 3 phase 3 Hp 230 V AC, 1 phase 5 Hp 230 V AC, 3 phase 5 Hp 460/575 V AC, 1 phase 5 hp 460/575 V AC, 3 phase Number of poles 2 Permissible voltage 575 V AC Pressure actuator Diaphragm Pressure setting range 215...250 psi (1482.37...1723.69 kPa) Net Weight 2.25 lb(US) (1.02 kg) 32...215 psi (220.63...1482.37 kPa) Range on decreasing pressure DPST Switch function Width 3.44 in (87.38 mm)

Range of Product

Switch application

Environment

NEMA Degree of Protection	NEMA 1
Product Certifications	UL listed file E12158 CCN NKPZ CSA file LR25490

Ordering and shipping details

Category	21536-9013 G COMMERCIAL PRESSURE SWITCH
Discount Schedule	CP7G
GTIN	785901160281
Nbr. of units in pkg.	1
Package weight(Lbs)	32.00 oz (907.185 g)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	10.16 in (25.806 cm)	
Package 1 width	4.00 in (10.16 cm)	
Package 1 Length	25.81 in (65.548 cm)	

Offer Sustainability

onor odolamability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEN RoHS
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	[™] End Of Life Information

Contractual warranty

Warranty	18 months