

All 3M Products Newsroom About 3M

Industrial Abrasives

Products Applications Industries Capabilities Support

<u>Un ted States</u> > <u>Manufacturing</u> > <u>Industrial Abrasives</u> > <u>Abrasives Product Catalog</u> > <u>Power Tools</u> > <u>Random Orb tal/Orbital Sanders</u> > 3M[™] Random Orb tal Sander 20317, 5 in Non-Vacuum 3/16 in Orb t, 1 per case

3M[™] Random Orbital Sander 20317, 5 in Non-Vacuum 3/16 in Orbit, 1 per case

3M ID 60440126898 UPC# 00051141203171 Part Number 20317



Our 3MTM Non-Vacuum Random Orbital Sanders are airpowered and deliver profess onal performance and a swirl-free finish in high-product on industrial environments where dust extraction is not required. Our high-quality tools are designed to optimize the performance of $3M^{TM}$ abrasives.

- Precis on-balanced steel workings run smoothly with less vibration, ideal for high production industrial environments
- Improved durabil ty, ergonomics and noise level maximize comfort and control for prolonged use
- Pneumatic power exceeds the capability of standard electric sanders, supplying hours of continual use
- Aluminum body and durable composite cover reduce cracked housings and downtime
- Low-profile, balanced design optimizes the performance of $3M^{\mbox{\tiny TM}}$ Abrasives

Overview

Engineered for performance and ergonomics, our family of $3M^{\text{TM}}$ Non-Vacuum Random Orb tal Sanders are loaded with features to reduce vibration and noise and provide greater wrist support and operator comfort. The comfortable rubber grip featuring proprietary $3M^{\text{TM}}$ Gripping Material, curved-throttle alloy steel lever, and built-in wrist support provide comfortable control, while the recessed lever platform eliminates pinch and pressure points on the operator's palm. The speed control dial is conveniently located on the s de and controlled w th the thumb. We've also lightened the load with a compos te cover that extends to the base to absorb and reduce vibration and keep these tools in serv ce by preventing cracked housings. An innovative internal muffler helps reduce noise and won't break off.

3M[™] Stikit[™] Disc Pad Included

We also include the 3M[™] Stikit[™] Disc Pad with these sanders. These pads reduce vibrat on, prov de excellent disc adhes on, and are designed to bring out optimal performance of these tools. The Stik t[™] system allows quick and easy disc removal. This Stikit disc pad is made of medium dens ty foam and has a 45 degree tapered edge, Stik t discs are sold separately. These versatile sanders also work great w th 3M[™] Hookit[™] Disc Pads, enabling operators to use our line Scotch-Brite[™] Surface Conditioning Discs as well.

Why use a 3M[™] Random Orbital Sander?

Our random orb tal sanders optimize sanding and surface preparation on many surfaces, including wood, metal prep for paint, fiberglass, compos te materials, and many other substrates. Also known as dual action (D/A) sanders, these industrial-grade tools rotate the abrasive disc and disc pad in two simultaneous overlapping oval patterns so no single abrasive particle follows the same path tw ce, resulting in a swirl-free finish, even when sanding against the grain.

Pneumat c sanders are also called air sanders and run on power generated by an air compressor. These include non-vacuum (NV), central vacuum (CV), and self-generated vacuum (SGV) models. Non-vacuum models such as these are not connected to a vacuum system and are used in applications where dust extract on is not a concern.



Metal fabrication application

Specifications

Airflow Rate	17 SCFM
Airflow Rate (metric)	481 LPM
Applications	Grinding, Finishing, Sanding
Brand	3M™
Converted Form	Power Tool
Equipment - Machines	Random Orbital Sanders
Height	3.26 Inch
Height (Metric)	82.9 mm
Industries	Marine, Metalworking, Transportation & Heavy Equipment, General Industrial, Paint Preparation, MRO, Aerospace, AOEM, Woodworking, Compos te
Length	5.89 Inch
Length (Metric)	149.6 mm
Max RPM	12000
Mineral Type	Aluminum Ox de
Motor HP (W)	.28 (209)
Orbit Diameter	0.18 Inch
Orbit Diameter (metric)	5 mm
Pad Included	Stikit™ Pad 20351
Power Type	Pneumatic
Product Form	Power Tool
Sub Industries	Primary Wood and Panel Processing, Custom Woodworking and Millwork, Cabinetry, Furn ture, Metal Fabrication
Weight Pound (kg)	1.65 (.75)