



## **FINISHES**

- 1. BODY & NUT = GOLD PLATE PER ASTM B488-11, TYPE II, 30 $\mu$ in MIN, GRADE C, OVER 50 TO 100 $\mu$ in STRESS FREE NICKEL PER AMS-QQ-N-290.
- 2. CONTACTS = GOLD PLATE PER ASTM B488-11, TYPE II, 50µin MIN, GRADE C, OVER 100 TO 200µin STRESS FREE SULFAMATE NICKEL PER AMS-QQ-N-290.
  3. ALL OTHER METAL PARTS = GOLD PLATE PER ASTM B488-11, TYPE II, 30µin MIN, GRADE C
- OVER 100 TO 200 µin COPPER STRIKE PER AMS 2418.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		DWN: D.N. CHKD:	N. 03/19/18  This document cannot be reproduced or communicated to a third party without prior					
		OTTIVE.	DAIL	written permission of RADIALL.				
DECIMAL	ANGLE	J.S.	03/19/18	SMA RIGHT ANGLE JACK				
		APVD:	DATE			LKHEAD P.C.B. MOUNT RECEPTACLE		
		J.M.	03/19/18					
REFERENCE:		MATERIALS & F	INISHES:	SIZE	FSCM NO.	DWG NO.		REV
ORIGINATED: D.N.		SEE NOTES		Α	19505	9695-1513	5-000	А
DATE: 03/19/18				SCALE 4:1		THIRD ANGLE PROJECTION	ANGLE SHEET 1 OF 1	