Product data sheet Characteristics

ZCKL8H7

Limit switch body, Limit switches XC Standard, ZCKL, 2 NO, slow break, 1/2"NPT



Main

- Iviaiii	
Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch body
Device short name	ZCKL
Body type	Fixed
Product Compatibility	XCKL
Associated head	ZCKD029 ZCKD59 ZCKD02 ZCKD02 ZCKD23 ZCKD21 ZCKD239 ZCKD10 ZCKD109 ZCKD41 ZCKD41 ZCKD41 ZCKD41 ZCKD41 ZCKD06 ZCKD16 ZCKD16 ZCKD15 ZCKD15 ZCKD15 ZCKD15 ZCKD08 ZCKD05 ZCKD17 ZCKD219
Body Material	Metal
Cable entry	1 entry tapped for 1/2" NPT conduit
Number of poles	2
Contacts type and composition	2 NO
Contact operation	Slow-break, simultaneous
Number of steps	1 1 position
Contacts material	Silver plated contacts

Complementary

Complementary	
Local display	Without
Electrical connection	Screw-clamp terminals 1 x 0.52 x 2.5 mm ²
Positive opening	Without
Minimum actuation speed	6 m/min
[le] rated operational current	3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A 0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	500 V 3)IEC 60947-1 contact block 300 VCSA C22.2 No 14 contact block 300 VUL 508 contact block
Maximum resistance across terminals	0.25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	4 KV IEC 60664 4 kV IEC 60947-1
Short-circuit protection	6 A cartridge fuse gG
Electrical durability	5000000 Cycles, DC-13 120 V, 1 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 3 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 2 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Width	2.05 in (52 mm)
Height	2.83 in (72 mm)
Depth	1.18 in (30 mm)

Net Weight	0.46 lb(US) (0.21 kg)
Terminals description ISO n°1	(21-22)NC (31-32)NC (13-14)NO
Environment	
IP Degree of Protection	IP66
IK Degree of Protection	IK05
Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment
• • • • • • • • • • • • • • • • • • • •	
Ordering and shipping details Category	22449-LIMIT SWITCHES,ACCESSORIES
Discount Schedule	T
GTIN	3389118130135
Nbr. of units in pkg.	1
· · ·	
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	US
Packing Units	
Package 1 Height	0.010 dm
Package 1 width	0.010 dm
Package 1 Length	0.020 dm
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☐ REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	₽roduct Environmental Profile
Contractual warranty	
The second real second	40 11

18 months

Warranty