Product data sheet Characteristics

NSYS3D12630

Spacial S3D plain door w/o mount.plate. H1200xW600xD300 IP66 IK10 RAL7035.





Main	
Range	Spacial
Product name	Spacial S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	47.24 in (1200 mm)
Enclosure nominal width	23.62 in (600 mm)
Enclosure nominal depth	11.81 in (300 mm)
Door type	Solid
Mounting plate description	Without mounting plate
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	1 body 1 door 1 lock 1 cable gland plate

Complementary

Complementary		
Body type	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	Front face 1	
Door opening side	Reversible 120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws	
Material	steel	
Surface finish	Epoxy-polyester powder	
Color	Gray RAL 7035)	
Standards	IEC 62208	
Product Certifications	GL UL LR BV CUL DNV	
Net Weight	76.06 lb(US) (34.5 kg)	

Environment

NEMA Degree of Protection	NEMA 4X/13
IK degree of protection	IK10 IEC 62262
IP degree of protection	IP66 IEC 60529



Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480159947
Nbr. of units in pkg.	1
Package weight(Lbs)	77.16 lb(US) (35.0 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
	T OE
Package 1 Height	14.17 in (36.0 cm)
Package 1 width	24.61 in (62.5 cm)
Package 1 Length	48.43 in (123.0 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	6
Package 2 Weight	487.22 lb(US) (221.0 kg)
Package 2 Height	78.74 in (200.0 cm)
Package 2 width	31.50 in (80.0 cm)
Package 2 Length	48.82 in (124.0 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) CEU RoHS
Mercury free	Yes
RoHS exemption information	₫ Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty

18 months