Quick Setup Guide for Sensor Hub - Nano

with Infineon Barometric Pressure Sensor (V2.0)

EVAL SHNBV01 DPS310 EVAL SHNBV01 DPS368







Infineon



Quick Setup for Digital Pressure Sensor Demo

STEP1

Box Content

Programmed Sensor Hub Nano with DPS310, DPS368





www.infineon.com/pressure sensor

STEP2

Install Infineon Toolbox

Detailed instruction and download option:

www.infineon.com/toolbox

Set update site:

For Infineon internal: "http://toolbox.intra.infineon.c om/updatesite/stable"

For external customers: "https://toolbox.infineon.com/s table"



Go to "manage tools" and download "Pressure Sensor Kit"



Download "Infineon

Toolbox"

Receive board

STEP3

Download GUI software

"SES2G Sensor Software Analyzer" (or use pre-installed software on Infineon Toolbox platform)

Unzip and Install

Double Click on

E Setup-SensorEvaluation

this self-extracts the software into a new folder, explore the new folder and double click on

Setup-SensorEvaluation

This will install the application in Windows.

STEP4

Before Launching the GUI you must pair over Bluetooth

Launch Bluetooth Device Manager in Windows

If IFX_NANOHUB is already paired please remove it by clicking on Remove device button

Otherwise make a new pairing of IFX_NANOHUB by clicking on

Add Bluetooth or other device

Click on "Add a device"

- Bluetooth (mice, keyboard, pens, or other kind of Bluetooth devices)
- A list of found device(s) will be refreshed
- Select IFX_NANOHUB and connection will be established,

Restart your computer before using the SES2G Sensor Software Analyzer to ensure full functionality

Download software and install

Pair your device via Bluetooth



Quick Setup for Digital Pressure Sensor Demo



Copyright © Infineon Technologies AG 2019. All rights reserved.



Part of your life. Part of tomorrow.

