



2 CONTACTS
 BLUE FEMALE HOUSING FOR WIRE INSULATION Ø1.00 TO Ø1.30

TOLERANCE UNLESS OTHERWISE SPECIFIED	
.X	±0.38
.XX	±0.25
.XXX	±0.13



THIS IS A C.A.D. GENERATED DRAWING
 DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER	
ORIGINAL	①



ISO 1:1



NOTE:

ELECTRICAL SPECIFICATIONS:

VOLTAGE RATING: 250V MAX.
 CURRENT RATING: 3A per CONTACT
 CONTACT RESISTANCE: 15mΩ MAX.
 INSULATOR RESISTANCE: 1000MΩ min.
 DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC(RMS)
 OPERATING TEMPERATURE: -40°C ~ 105°C

MATERIAL & FINISH:

HOUSING: PBT, UL94V-0
 CONTACTS: PHOSPHOR BRONZE, TIN PLATED
 SEALS: SILICONE RUBBER

560 SERIES WATERPROOF CONNECTOR		ACAD REFERENCE NO.: 560 Assembly	
		DRAWN: C.B	DATE: July 23, 2020
CHECKED:	DATE:		
SCALE: 2:1	SHEET 1 OF 1		
DRAWING NUMBER: 560 Assembly			ISSUE
PART NUMBER: 560-002-000-410			1



THIS SERIES FULLY CONFORMS TO
 THE EUROPEAN UNION DIRECTIVES
 2011/65/EU FOR RoHS COMPLIANCY.



EDAC INC
 TORONTO, ONTARIO
 CANADA

YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS
 ARE THE PROPERTY OF EDAC INC., AND
 SHALL NOT BE REPRODUCED, OR COPIED
 OR USED AS THE BASIS FOR THE
 MANUFACTURE OR SALE OF APPARATUS
 WITHOUT WRITTEN PERMISSION.