

## **UHF RFID Inlays**





Dimensions:

**Operating Frequency:** Global (860 - 960MHz) **RF Protocol:** ISO-18000-6C, EPC Class 1 Gen 2

Chip: NXP UCODE 7

EPC Memory: 128 bit

**TID Memory:** 96 bit, pre- encoded for multi- vendor chip (MCS) based serialization, factory programmed

## 866-903- RFID (7343) / rfid.info@averydennison.com

## Common Applications:

- Apparel and Retail
- Supply Chain, Inventory and Logistics

Part Number	600411	600414
Format	Dry Inlay	Wet Inlay (pressure sensitive)
Antenna dimensions (CDxMD)	2.7560 0.571 in [70.5 x 14.5mm]	2.7560 0.571 in [70.5 x 14.5mm]
Die- cut dimensions	N/ A	2.881 x 0.696 in [73 x 18 mm]
Inlay substrate material	PET	PET
Inlay- to- liner adhesive	N/ A	S-490 (FASSON)
Liner material	N/ A	1.5 M PET
Face sheet	N/ A	N/ A
Standard pitch	0.875 in [22.23mm]	0.875 in [22.23mm]
Standard web width	3.75 in [95.25 mm]	3.0 in [76.2 mm]
Total thickness over chip	10 -13 mils [254 - 330.2 microns]	10 -13 mils [254 - 330.2 microns]
Operating temperature	-40 to 185F [-40 to 85C]	-40 to 185F [-40 to 85C]
RoHS	EU Directive 2002/95/ EC	EU Directive 2002/95/ EC
Quality assurance	Compliant 100% read tested with out- of tolerance inlay marked	Compliant 100% read tested with out- of tolerance inlay marked
Un- wind direction	Inlay - side Out	Inlay - side Out
Core size with adaptor insert	6 in [152.4mm]	3 in [76.2mm]
Maximum roll outer diameter (not to exceed)	17in [431.8mm]	13 in [330.2mm]
Average # of units per roll	40,000	10,000
Rev	00	00

CARE AND HANDLING RFID inlays are sensitive to ESD. Observe standard practices to keep environmental static charge to a minimum.

APPLICATIONS This product should be tested by the customer/ user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use.

WARRANTY Please refer to Avery Dennison RFID standard terms and conditions. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

PRODUCT CHANGES Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice.

TRADEMARK STATEMENT Avery Dennison, S490 and Fasson are trademarks of Avery Dennison Corporation. For the most recent information on Avery Dennison products, visit www.rfid.averydennison.com.

© 2014 Avery Dennison Inc. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342