



**WIRING**

TIP - TIP

RING - RING

SLEEVE - SLEEVE

**LONG FRAME  
MOLDED PLUG**

**CABLE LENGTH**

- 1 = 1 FOOT LONG
- 2 = 2 FEET LONG
- 3 = 3 FEET LONG
- 4 = 4 FEET LONG
- 5 = 5 FEET LONG
- 6 = 6 FEET LONG
- 7 = 7 FEET LONG
- 8 = 8 FEET LONG
- 9 = 9 FEET LONG
- 10 = 10 FEET LONG
- 11 = 11 FEET LONG
- 12 = 12 FEET LONG

**X**

**RoHS COMPLIANT**

**CABLE JACKET COLOR**

- BK = BLACK
- BL = BLUE
- GN = GREEN
- GY = GRAY
- O = ORANGE
- P = PURPLE
- R = RED
- Y = YELLOW

**NOTES:**

**1. MATERIALS:**

- PLUG - COPPER ALLOY, NICKEL PLATED
- INSULATORS - THERMOPLASTIC, BLACK
- OVERMOLD - THERMOPLASTIC, BLACK
- CABLE - 24 AWG, 110 OHM, PVC JACKET

**2. THESE PRODUCTS ARE RoHS COMPLIANT.**

**CUSTOMER DRAWING**

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.						
					SIZE	WIDTH	MULT	LBS/M	TEMPER		
					UNLESS OTHERWISE SPECIFIED			FINISH			
					1. ALL DIMENSIONS IN INCHES [mm]			MATERIAL			
					- TWO PLACE DECIMALS ±0.02 [0.5]			SPEC No.			
					- THREE PLACE DECIMALS ±0.005 [0.13]			SCALE			
					FIRST USED ON			1:1			
B	28261	02/11/20	PC	TK	DATE DRAWN	BY	CHKD	APVD	<b>Switchcraft®</b>		
A	26228	4/3/07	TJK	TJK	2/10/12	TJK	TJK	TJK			
REV					ECO NUMBER		DATE	BY	APVD	SHEET 1 OF 1	
REVISIONS					DO NOT SCALE DRAWING					PART No.	REV
					3 CONDUCTOR					LF_X SERIES	B
					Ø0.25 LONGFRAME PATCHCORD						

SolidWorks CAD File

