## Miniature Incandescent Indicators



T-3 1/4 MINIATURE BAYONET BASE

See lamp ratings on page K.

Recognized under the component program of Underwriters' Laboratories Inc.

75W., 125V.



How to designate the three digit part number suffix (-XXX)

| FINISH                                                                          | RESISTOR | HARDWARE                                                                               |
|---------------------------------------------------------------------------------|----------|----------------------------------------------------------------------------------------|
| 1 — White nickel<br>2 — Black nickel<br>3 — Polished chrome<br>4 — Satin chrome | 0 — None | <ul><li>1 — Brass</li><li>3 — Water-tight, on<br/>the face of the<br/>panel.</li></ul> |

NOTE: The part numbers given in this catalog indicate **standard** indicator lights. The table above provides the standard and optional designations for **Finish** and **Hardware** where appropriate. Example: 95–1310–0931–203 (black nickel finish with water-tight construction).


Part numbers listed in this catalog designate products with RED lens. For ordering lens colors other than red, consult chart on page 2D.

## FOR MOUNTING IN 11/16" CLEARANCE HOLE FOR 2 TO 120V OPERATION

## MATERIALS AND FINISHES

- Mounting Bushing and Lens Holder: Standard—Brass, polished chrome. Optional—White nickel, black nickel or satin chrome finish.
- Mounting Nut: Brass, white nickel finish.
- Internal-tooth Lockwasher: Phosphor bronze, white nickel finish.
- Terminals: Solder -Brass, hot tinned with elongated slot.
   Screw-Brass, white nickel finish.
   Quick Connect-Brass, tinned. Mate with standard female receptacles.

These assemblies also accommodate T-3 bulbs with miniature bayonet base, incandescent—in voltages from 6-120V. When lamps rated 2 watts or over are used, lens caps of high temperature plastic are required. Contact the factory for additional data and correct catalog number designations.



26-0410-1111-301 Screw-in lens cap

## WITH SCREW-IN LENS CAPS

| solder terminals                                                                                                                                                                                                                                                                             | screw terminals      | quick connect terminals |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-------------------------|
| 1/16 X 13/16 O.D. FLANGE 1/16 FANEL (REF.) -0.30 JOS X 61/64 - 010 O.D. INTERNAL TOOTH LOCKWASHER 3/3/X 13/16 AROSS FLATS HEX. NUT 13/16 27 NS THO. MOUNTING BUSHING + SIGM MARKED ON THE TERMINAL COUNTECTE TO THE CENTER CONTACT.  5/64 X 1/6 S.O.TS  PROJECTION BACK OF PANEL 14/1/64 MAX | SCREWS No. 4-36 THD. | 1/16 DIA<br>HOLES       |
| 26-0410-11-301                                                                                                                                                                                                                                                                               | 26-1310-11-301       | 26-5710-11-301          |

BASE PART NUMBERS

26 SERIES

CAP PART NUMBERS

COMPLETE ASSEMBLY PART NUMBERS

TO STOVEPIPE

9/16 - 27 NS THD.

26-1131-300 transparent 26-1191-300 internal fluting 26-1111-300 back frosted 26-0410-1131-301 26-131 26-0410-1191-301 26-131 26-0410-1111-301 26-131

26-1310-1131-301 26-1310-1191-301 26-1310-1111-301 26-5710-1131-301 26-5710-1191-301 26-5710-1111-301

These assemblies should be specified when lamps rated over 2 watts are used.

Part numbers shown in gray are normally in inventory at your Dialight Distributor.