PCIE-1154 PCIE-1158

4-port PCI Express USB Vision Frame Grabber

8-port PCI Express USB Vision Frame Grabber



Features

- Four independent USB 3.0 controllers Renesas µPD720202
- PCI Express Gen2 x4 interface, up to 2.0 GB/s
- eFuse power protection
- Protective shell prevents damage to components
- Supports Microsoft Windows 10

Introduction

Advantech's PCIE-1158 is an 8 x port PCIe x4 expansion card based on 4 x Renesas µPD720202 USB 3.0 host controllers for industrial and machine vision applications that require high transfer speeds. PCIE-1158 features 8 x USB 3.0 ports with 900-mA current to ensure stable power for external USB devices. It is a high-bandwidth industrial-grade expansion card designed for connecting USB 3.0 industrial cameras in machine vision, factory automation, and medical applications.

Specifications

USB

005	
Interface	PCI Express x4
 Connector 	8 x USB 3.0 Type A (PCIE-1158-AE only)
 Host Bus 	4-lane Gen 2.0 PCIe interface, compliant with
- Controller	PCI Express Base Specification, Revision 2.0 Renesas µPD720202, Compliant with USB 3.0 Specification and Intel® xHCI Specification, Revision 1.0
 Max Current 	900 mA maximum per port
 Data Transfer Rate 	SuperSpeed; High Speed; Full Speed; Low Speed
 Power 	5 V_{DC} power output, max. 4.5W per port
Power Requirements	
 Input Voltage 	12 V_{DC} direct from PCIe slot (limited to PCIe design) or AT/ATX system power input
 Overload Current Protection 	Device auto recover after eFuse tripped when rated currents > 2A
Environment	
 Operating Temperature Storage Temperature Operating Humidity 	0 ~ 60 °C (32 ~ 140 °F) -20 ~ 80 °C (-4 ~ 176 °F) 5 ~ 95% RH
Mechanics	
 Dimensions (W x D) Net Weight 	153 x 106 mm (6.02 x 4.17 in) 300 g (.66 lb)
Certification Compliance 	FCC CE Class A
Operating Systems	
= OS	Microsoft Windows 10

Ordering Information

Frame Grabber

- PCIE-1158-AE
- PCIE-1154-BE(Preliminary) 4-port PCIe USB Vision Frame Grabber

Optional Cable

- 1700025427-01
- 1700025428-01
- 170304015K

4-port PCIe USB Vision Frame Grabber

8-port PCIe USB Vision Frame Grabber

USB 3.0 cable, 5 m, Micro B (locking) to Type A USB 3.0 cable, 3 m, Micro B (locking) to Type A A Cable 2*2P-4.2/B4P-5.08*2 15CM