

Mounting frame - SI-M1A-ML - 1407588

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Mounting frame for one front plate/socket, frame: black, cover: metallic, closed with 3 mm two-way key bit.



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	120.0 g
Custom tariff number	85389099
Country of origin	Czech Republic

Technical data

Ambient conditions

Ambient temperature (operation)	-30 °C 70 °C

General

Туре	For 1 front plate
Housing material	PBT
Flammability rating according to UL 94	V0

Standards and Regulations

Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27143424



Mounting frame - SI-M1A-ML - 1407588

Classifications

eCl@ss

eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27189234

ETIM

ETIM 3.0	EC000441
ETIM 4.0	EC002625
ETIM 5.0	EC002625

UNSPSC

UNSPSC 6.01	30211808
UNSPSC 7.0901	39121408
UNSPSC 11	39121408
UNSPSC 12.01	39121408
UNSPSC 13.2	39121408

Approvals

Α	n	n	ro	va	ls
, v	\sim	\sim	•	٧u	·

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details


EAC

Drawings



Mounting frame - SI-M1A-ML - 1407588

Dimensional drawing



Panel cutout

Phoenix Contact 2016 @ - all rights reserved http://www.phoenixcontact.com