

SmartRack 2U Hinged Wall-Mount Patch Panel Bracket, TAA

MODEL NUMBER: N060-002



Highlights

- Laser cut 14-gauge steel results in smooth edges
- Keyholes on 16-inch centers plus through-the-wall cabling cut-out
- Accepts any standard 19inch Patch Panels
- 2U Height (3.50"): 19"wide x 3.50" high x 6.0" deep
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Package Includes

- 2U Wallmount Patch Panel Bracket
- Pkg 10 mounting screws

Description

Tripp Lite's heavy duty 14-gauge steel, 2U (3.50") wall mount patch panel bracket, is the ideal alternative to a full size rack. Standard EIA 19-inch width allows installation of any 19inch patch panel. Laser cut metal (not punched) keeps all edges smooth, greatly reducing the possibility of injury, and, wear on cable jackets. Universal mounting for right or left hinging. Keyholes are spaced 16inches for mounting on wall studs. Stamped, horizontal reinforcement ribs allow for greater sturdiness and stability, and allow the addition of a rear cutout for feeding cable through a wall opening. Smooth, glossy black finish.

Features

- 2U Height (3.50"), 6inch depth
- Laser cut for smooth edges
- 16 -inch center mounting
- Universal left or right hinge mounting
- Rear cut-out for through the wall cabling
- Standard EIA 19inch width accepts any manufacturers EIA compliant patch panel
- Smooth, black glossy finish
- Heavy duty 14 gauge steel with stamped reinforcement ribs

Specifications

| OVERVIEW | |
|-----------------|------------------|
| UPC Code | 037332126399 |
| Accessory Type | Mounting Bracket |
| Accessory Class | Rack Accessories |
| PHYSICAL | |

| | |
|-------------------------------------|--|
| Color | Black |
| Rack Height | 2U |
| Maximum Device Depth (cm) | 13.97 |
| Maximum Device Depth (in.) | 5.5 |
| Maximum Device Depth (mm) | 140 |
| Shipping Dimensions (hwd / in.) | 4.10 x 20.30 x 6.70 |
| Shipping Dimensions (hwd / cm) | 10.41 x 51.56 x 17.02 |
| Shipping Weight (lbs.) | 2.90 |
| Shipping Weight (kg) | 1.32 |
| Unit Dimensions (hwd / in.) | 0.000 x 0.000 x 0.000 |
| Unit Dimensions (hwd / cm) | 8.89 x 48.26 x 15.24 |
| Unit Weight (lbs.) | 2.5 |
| Unit Weight (kg) | 1.13 |
| Weight Capacity - Stationary (kg) | 8 |
| Weight Capacity - Stationary (lbs.) | 17 |
| STANDARDS & COMPLIANCE | |
| Product Certifications | IEC 60297-3; NOM (Mexico); UL 60950-1 |
| Product Compliance | DIN 41494; RoHS; EIA/ECA-310-E; Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |