Product data sheet Characteristics

NSYCCOHYT230VID

Climasys CC - electronic hygrotherm - 200... 240 V - temp -40...80 C - Hr 20...80%





Overview

Lead time	Usually Ships within 4 Weeks	
-----------	------------------------------	--

Main

Range	ClimaSys	
Product name	ClimaSys CC	
Product or Component Type	Electronic hygrotherm	
Temperature setting range	-40176 °F (-4080 °C)	
Humidity setting range	2080 %	
Display Type	OLED screen	
Information Displayed	Relative humidity Temperature in °F Temperature in °C	

Complementary

<u> - </u>		
Input voltage	200240 V AC	
Sensor Type	Optional NTC external sensor	
Maximum switching capacity	4 A 230 V AC	
Electrical connection	8 connectors 2.5 mm²	
Mounting Mode	Clipped By screws	
Height	External 3.35 in (85 mm)	
Width	External 2.20 in (56 mm)	
Depth	External 1.73 in (44 mm)	
Mounting Location	35 mm DIN rail Cross rails Spacial upright On mounting plate	
Ambient Air Temperature for Operation	-40176 °F (-4080 °C)	
Hysteresis	2 K programmed value	
Hysteresis	3 %	
Number of outputs	2 ventilation/heating function	
Material	PC	
Color	Light gray	
Flame retardance	Self-extinguishing conforming to UL94 (material V0)	
Product Certifications	UR	

Ordering and shipping details

ES1
201
3606480152597
1
5.40 oz (153.0 g)
Yes
ES

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	2.17 in (5.5 cm)	
Package 1 width	2.95 in (7.5 cm)	
Package 1 Length	3.35 in (8.5 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	[™] China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

Contractual warranty

Warranty	18 months
----------	-----------