


## High temperature 30 A, 600 V D<sup>2</sup>PAK thyristor SCRs



### Features

- High junction temperature:  $T_j = 150 \text{ }^\circ\text{C}$
- High noise immunity  $dV/dt = 1000 \text{ V}/\mu\text{s}$  up to  $150 \text{ }^\circ\text{C}$
- Gate triggering current  $I_{GT} = 15 \text{ mA}$
- Peak off-state voltage  $V_{DRM}/V_{RRM} = 600 \text{ V}$
- High turn-on current rise  $di/dt = 100 \text{ A}/\mu\text{s}$
- **ECOPACK2** compliant

### Applications

- General purpose AC line load switching
- Motorbike voltage regulator circuits
- Inrush current limiting circuits
- Motor control circuits and starters
- Heating resistor control, Solid State Relays
- Lighting

### Description

Thanks to its operating junction temperature up to  $150^\circ\text{C}$ , the **TN3015H-6G** SCR in D<sup>2</sup>PAK package offers high thermal performance operation up to 30 A RMS in a compact SMD design.

Its trade-off noise immunity ( $dV/dt = 1000 \text{ V}/\mu\text{s}$ ) versus its gate triggering current ( $I_{GT} = 15 \text{ mA}$ ) and its turn-on current rise ( $di/dt = 100 \text{ A}/\mu\text{s}$ ) allows to design robust and compact control circuit for voltage regulator in motorbikes and industrial drives, overvoltage crowbar protection, motor control circuits in power tools and kitchen appliances and inrush current limiting circuits.

| Product status    |                              |
|-------------------|------------------------------|
| <b>TN3015H-6G</b> |                              |
| Product summary   |                              |
|                   |                              |
| Order code        | TN3015H-6G                   |
| Package           | D <sup>2</sup> PAK           |
| $V_{DRM}/V_{RRM}$ | 600 V                        |
| $T_j$             | $150 \text{ }^\circ\text{C}$ |
| $I_{GT}$          | 15 mA                        |

## 1 Characteristics

**Table 1. Absolute maximum ratings (limiting values)**

| Symbol            | Parameter  |                        |                     | Value                   | Unit                   |
|-------------------|--|------------------------|---------------------|-------------------------|------------------------|
| $I_{T(RMS)}$      | RMS on-state current (180 ° conduction angle)  | $T_c = 127^\circ C$    |                     | 30                      | A                      |
| $I_{T(AV)}$       | Average on-state current (180 ° conduction angle)  | $T_c = 127^\circ C$    |                     | 19                      | A                      |
|                   |  | $T_c = 134^\circ C$    |                     | 15                      |                        |
|                   |  | $T_c = 141^\circ C$    |                     | 10                      |                        |
| $I_{TSM}$         | Non repetitive surge peak on-state current ( $T_j$ initial = 25 °C)                              | $t_p = 8.3 \text{ ms}$ |                     | 295                     | A                      |
|                   |  | $t_p = 10 \text{ ms}$  |                     | 270                     |                        |
| $I^2t$            | $I^2t$ value for fusing ( $T_j$ initial = 25 °C)   | $t_p = 10 \text{ ms}$  |                     | 364                     | $\text{A}^2\text{s}$   |
| $dI/dt$           | $I_G = 2 \times I_{GT}$ , $t_r \leq 100 \text{ ns}$<br>Critical rate of rise of on-state current | $f = 60 \text{ Hz}$    | $T_j = 25^\circ C$  | 100                     | $\text{A}/\mu\text{s}$ |
| $V_{DRM}/V_{RRM}$ | Repetitive peak off-state voltage  |                        |                     | 600                     | V                      |
| $V_{DSM}/V_{RSM}$ | Non repetitive surge peak off-state voltage  | $t_p = 10 \text{ ms}$  | $T_j = 25^\circ C$  | $V_{DRM}/V_{RRM} + 100$ |                        |
| $I_{GM}$          | Peak gate current  | $t_p = 20 \mu\text{s}$ | $T_j = 150^\circ C$ | 4                       | A                      |
| $P_{G(AV)}$       | Average gate power dissipation   |                        | $T_j = 150^\circ C$ | 1                       | W                      |
| $V_{RGM}$         | Maximum peak reverse gate voltage  |                        | $T_j = 25^\circ C$  | 5                       | V                      |
| $T_{stg}$         | Storage junction temperature range   |                        |                     | -40 to +150             | °C                     |
| $T_j$             | Maximum operating junction temperature   |                        |                     | -40 to +150             | °C                     |

**Table 2. Electrical characteristics ( $T_j = 25^\circ C$  unless otherwise specified)**

| Symbol   | Test conditions  |                     |                     | Value | Unit |
|----------|--|---------------------|---------------------|-------|------|
| $I_{GT}$ | $V_D = 12 \text{ V}$ , $R_L = 33 \Omega$   |                     |                     | Min.  | 6    |
|          |  |                     |                     | Max.  | 15   |
| $V_{GT}$ |  |                     | $T_j = 150^\circ C$ | Max.  | 1.3  |
| $V_{GD}$ | $V_D = V_{DRM}$ , $R_L = 3.3 \text{ k}\Omega$  |                     | $T_j = 150^\circ C$ | Min.  | 0.15 |
| $I_H$    | $I_T = 500 \text{ mA}$ , gate open   |                     |                     | Max.  | 60   |
| $I_L$    | $I_G = 1.2 \times I_{GT}$  |                     |                     | Max.  | 75   |
| $dV/dt$  | $V_D = 402 \text{ V}$ , gate open  |                     | $T_j = 150^\circ C$ | Min.  | 1000 |
| $t_{gt}$ | $I_T = 60 \text{ A}$ , $V_D = 600 \text{ V}$ , $I_G = 100 \text{ mA}$ , $(dI_G/dt)_{\text{max}} = 0.2 \text{ A}/\mu\text{s}$                                   |                     |                     | Typ.  | 1.9  |
| $t_q$    | $I_T = 30 \text{ A}$ , $V_D = 402 \text{ V}$ , $(di/dt)_{\text{off}} = 30 \text{ A}/\mu\text{s}$ , $V_R = 25 \text{ V}$ , $dV_D/dt = 50 \text{ V}/\mu\text{s}$ | $T_j = 150^\circ C$ |                     | Typ.  | 80   |

**Table 3. Static characteristics**

| Symbol             | Test conditions                                |                           | Value | Unit                |
|--------------------|--|---------------------------|-------|---------------------|
| $V_{TM}$           | $I_{TM} = 60 \text{ A}, t_p = 380 \mu\text{s}$ | $T_j = 25^\circ\text{C}$  | Max.  | 1.6                 |
| $V_{TO}$           | Threshold voltage                              | $T_j = 150^\circ\text{C}$ | Max.  | 0.84                |
| $R_D$              | Dynamic resistance                             | $T_j = 150^\circ\text{C}$ | Max.  | 14 $\text{m}\Omega$ |
| $I_{DRM}, I_{RRM}$ | $V_D = V_{DRM}, V_R = V_{RRM}$                 | $T_j = 25^\circ\text{C}$  | Max.  | 10 $\mu\text{A}$    |
|                    |  | $T_j = 150^\circ\text{C}$ | Max.  | 5 $\text{mA}$       |


**Table 4. Thermal parameters**

| Symbol        | Parameter  |      | Value | Unit               |
|---------------|--|------|-------|--------------------|
| $R_{th(j-c)}$ | Junction to case (DC)                                      | Max. | 0.85  | $^\circ\text{C/W}$ |
| $R_{th(j-a)}$ | Junction to ambient <sup>(1)</sup> $S(1) = 1 \text{ cm}^2$ | Typ. | 45    |                    |


1. S : Copper pad under tab, on PCB FR4

## 1.1 Characteristics curves


**Figure 1. Maximum power dissipation versus average on-state current**




**Figure 2. Average and DC on-state current versus case temperature**




**Figure 3. Average and D.C. on state current versus ambient temperature**




**Figure 4. On-state characteristics (maximum values)**




**Figure 5. Relative variation of thermal impedance junction to case and junction to ambient versus pulse duration**




**Figure 6. Relative variation of gate trigger current and gate voltage versus junction temperature (typical values)**




**Figure 7. Relative variation of holding and latching current versus junction temperature (typical values)**




**Figure 8. Relative variation of static dV/dt immunity versus junction temperature (typical values)**




**Figure 9. Surge peak on-state current versus number of cycles**




**Figure 10. Non repetitive surge peak on-state current for a sinusoidal pulse with width t<sub>p</sub> < 10 ms**



**Figure 11. Relative variation of leakage current versus junction temperature**



**Figure 12. Thermal resistance junction to ambient versus copper surface under tab**




## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.

### 2.1 D<sup>2</sup>PAK package information

- ECOPACK®2 compliant
- Lead-free package leads finishing
- Molding compound resin is halogen-free and meets UL standard level V0

Figure 13. D<sup>2</sup>PAK package outline





(1) Resin gate is accepted in each of position shown on the drawing, or their symmetrical.

Table 5. D<sup>2</sup>PAK package mechanical data

| Ref.              | Dimensions  |      |       |                       |        |        |
|-------------------|-------------|------|-------|-----------------------|--------|--------|
|                   | Millimeters |      |       | Inches <sup>(1)</sup> |        |        |
|                   | Min.        | Typ. | Max.  | Min.                  | Typ.   | Max.   |
| A                 | 4.30        |      | 4.60  | 0.1693                |        | 0.1811 |
| A1                | 2.49        |      | 2.69  | 0.0980                |        | 0.1059 |
| A2                | 0.03        |      | 0.23  | 0.0012                |        | 0.0091 |
| A3                |             | 0.25 |       |                       | 0.0098 |        |
| b                 | 0.70        |      | 0.93  | 0.0276                |        | 0.0366 |
| b2                | 1.25        |      | 1.7   | 0.0492                |        | 0.0669 |
| c                 | 0.45        |      | 0.60  | 0.0177                |        | 0.0236 |
| c2                | 1.21        |      | 1.36  | 0.0476                |        | 0.0535 |
| D                 | 8.95        |      | 9.35  | 0.3524                |        | 0.3681 |
| D1                | 7.50        |      | 8.00  | 0.2953                |        | 0.3150 |
| D2                | 1.30        |      | 1.70  | 0.0512                |        | 0.0669 |
| e                 | 2.54        |      |       | 0.10000               |        |        |
| E                 | 10.00       |      | 10.28 | 0.3937                |        | 0.4047 |
| E1                | 8.30        |      | 8.70  | 0.3268                |        | 0.3425 |
| E2                | 6.85        |      | 7.25  | 0.2697                |        | 0.2854 |
| G                 | 4.88        |      | 5.28  | 0.1921                |        | 0.2079 |
| H                 | 15          |      | 15.85 | 0.5906                |        | 0.6240 |
| L                 | 1.78        |      | 2.28  | 0.0701                |        | 0.0898 |
| L2                | 1.27        |      | 1.40  | 0.0500                |        | 0.0551 |
| L3                | 1.40        |      | 1.75  | 0.0551                |        | 0.0689 |
| R                 |             | 0.40 |       |                       | 0.0157 |        |
| V2 <sup>(2)</sup> | 0°          |      | 8°    | 0°                    |        | 8°     |

1. Dimensions in inches are given for reference only

2. Degrees

Figure 14. D<sup>2</sup>PAK recommended footprint (dimensions are in mm)Figure 15. D<sup>2</sup>PAK stencil definitions(dimensions are in mm)

### 3 Ordering information

Figure 16. Ordering information scheme




Table 6. Ordering information

| Order code    | Marking   | Package            | Weight | Base qty. | Delivery mode |
|---------------|-----------|--------------------|--------|-----------|---------------|
| TN3015H-6G-TR | TN3015H6G | D <sup>2</sup> PAK | 1.5 g  | 1000      | Tape and Reel |
| TN3015H-6G    |           |                    |        | 50        | Tube          |

## Revision history

**Table 7. Document revision history**

| Date        | Revision | Changes          |
|-------------|----------|------------------|
| 05-Jul-2019 | 1        | Initial release. |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to [www.st.com/trademarks](http://www.st.com/trademarks). All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2019 STMicroelectronics – All rights reserved