



Product: <u>83349E</u> ☑

Electronic, 4 C #22 Str SPC, TFE Ins, OA SPC Brd, TFE Tape Jkt, MIL-W-16878/4 (Type E)

😭 Request Sample

Product Description

High Temperature Electronic, 4 Conductor 22AWG (19x34) Silver Plated Copper, TFE Insulation, Overall Silver Plated Copper Braid(85%) Shield, TFE Tape Outer Jacket, MIL-W-16878/4 (Type E)

Technical Specifications

Product Overview

Conductor(s) 4 sulation Image: Conductor (s) Conductor(s) PT uter Shield Image: Conductor (s) Shield Type Image: Conductor (s) Gradd Silver	Material TFE - Polytetrafluoroe	Coverag	Nom. Thick 0.010 in (0.2		nsulation Diameter	Color Code White, Black, Red, Green	
Conductor(s) 4 nsulation Element Conductor(s) PT Outer Shield Shield Type Braid Silv	Material TFE - Polytetrafluoroo Material	22 AWG ethylene Coverag	19x34 Nom. Thick 0.010 in (0.2	SC - Silvered C kness Nom. In	nsulation Diameter		
Conductor(s) PT Duter Shield Shield Type	Material TFE - Polytetrafluoroe Material	ethylene	Nom. Thick 0.010 in (0.2	kness Nom. Ir	nsulation Diameter		
Element Conductor(s) PT Duter Shield Shield Type Braid	TFE - Polytetrafluoroe Material	Coverag	0.010 in (0.24				
Conductor(s) PT Duter Shield Shield Type Braid Silv	TFE - Polytetrafluoroe Material	Coverag	0.010 in (0.24				
Duter Shield Shield Type Braid Silv	Material	Coverag		25 mm) 0.05 in	(1.3 mm)	White, Black, Red, Green	
Shield Type Braid Silv			е				
Braid Silv			е				
	lvered Copper (SC)	85%					
Outer Jacket							
Materia	ial Nom	n. Thickn	ess Nom.	. Diameter			
PTFE - Polytetrafluoroethylene 0.011 in (0.28 mm) 0.163 in (4.14 mm)							
Overall Cable Dia	ameter (Nominal): 0.	.163 in (4.	.14 mm)				
Electrical Cha	aracteristics						
ectricals							
	om. Conductor DCR			Cond-to-Cond		e Cond-to-Other (Conds +	Max. Current

Voltage

Voltage Rating 600 V

Mechanical Characteristics

Temperature UL Temperature Operating 200°C -65°C to +200°C Bend Radius Stationary Min. Installation Min. 1.63 in (41.4 mm) 1.63 in (41.4 mm)

Max. Pull Tension:	38 lbs (17 kg)
Bulk Cable Weight:	26 lbs/1000ft

Standards and Compliance

Sustainability:	CA Prop 65
CPR Compliance:	CPR Euroclass: Eca
NEMA Compliance:	NEMA HP3
Military Compliance:	MIL-W-16878/4 (Type E except stranding), (insulated conductors)
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.
History	

Update and Revision:

Revision Number: 0.524 Revision Date: 01-20-2023

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
83349E 009100	White			612825204374
83349E 0091000	White	Reel	1,000 ft	612825204381

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.