

PL602-20-K52

Programming Specification

OPERATING PARAMETERS

	Input Clock (MHz)	CLK	Operating Voltage (V)	
		Frequency (MHz)	Accuracy (ppm)	Operating Voltage (V)
	100	100	0	3.3

PIN DESCRIPTION

Name	Pin #	Туре	Description	Package Pin Configuration	
CLK1	1	0	Programmable Clock Input		
GND	2	Р	GND Connection	CLK1 CLK0	
FIN	3	I	Reference Input		
OE	4	I	Output Enable Input		
VDD	5	Р	VDD Connection	FIN 3 8 4 OE	
CLK0	6	0	Programmable Clock Output	SOT23-6L	

Note: please refer to PhaseLink's PL602-20T datasheet for detailed electrical specifications.

ORDERING /SHIPPING INFORMATION

Package Option	Temp. Range	Shipping Method	
SOT23	Commercial	T&R	

Part/Order Number	Verification Code	Marking
PL602-20-K52TC	02-02-04-01-60-40-00-00-33	C9K52 LLL

For Package/Marking specifications please see Packaging Spec. Note: LLL / LLLLL designate Production Lot.

PhaseLink Corporation, reserves the right to make changes in its products or specifications, or both at any time without notice. The information furnished by Phaselink is believed to be accurate and reliable. However, PhaseLink makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of whatever nature resulting from the use of, or reliance upon this product. LIFE SUPPORT POLICY: PhaseLink's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of PhaseLink Corporation.

PhaseLink Corp. 2880 Zanker Rd., Suite 103, San Jose, California 95134 Tel (408) 571-1668 www.phaselink.com Rev. 10/15/10