
## XUSZMF202

Telemecanique Safety light curtains XUSL, Column with mirror 1970 mm for light curtains, Hp = 1810 mm





#### Main

Main	
Range of Product	Telemecanique Safety light curtains XUSL
Accessory / separate part category	Mounting and fixing accessories
Accessory / Separate Part Type	Fixing column
Offer type	With mirror
Product Compatibility	XUSL.E136 to XUSL.E181
Accessory / separate part destination	Safety light curtain type 2 Safety light curtain type 4

## Complementary

1	
Ambient Air Temperature for Operation	-22131 °F (-3055 °C) -22131 °F (-3055 °C)
Ambient Air Temperature for Storage	-22158 °F (-3070 °C) -22158 °F (-3070 °C)
Column height	77.56 in (1970 mm)
Height protected	71.26 in (1810 mm)
Net Weight	19.84 lb(US) (9 kg)
Net Weight	19.84 lb(US) (9 kg)

## Ordering and shipping details

Category	22455-LIGHT CURTAINS - XUSL
Discount Schedule	DS2
GTIN	3389119619189
Nbr. of units in pkg.	1
Package weight(Lbs)	23.15 lb(US) (10.5 kg)
Returnability	No
Country of origin	IT

## Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	5.51 in (14 cm)	
Package 1 width	7.87 in (20 cm)	
Package 1 Length	81.10 in (206 cm)	


## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

# XUSZMF202

## **Dimensions**

### With XUSZFB2



## With XUSZFB1

