

Product Change Notice (PCN)

Subject: Alternate Die Attach Material for Assembly of Intersil Hermetic Packaged Products

Publication Date: 9/30/2016 Effective Date: 12/30/2016

Revision Description:

Initial Release

Description of Change:

This notice is to inform you that Intersil has qualified the Henkel QMI 2569 silver glass adhesive as an alternate die attach material for assembly of hermetic packaged products at its Palm Bay, FL facility. The QMI 2569 die attach material will be used as an alternate to the JM7000 Silver Polymer material in use today for the listed products. This action will expand current capabilities and capacities to optimize Intersil's ability to meet customer's delivery requirements. The product and material qualification activity is complete.

Reason for Change:

The Henkel QMI 2569 die attach material provides improved thermal characteristics as well as improved wire bonding process control (less volatile outgassing during the cure process). Intersil has qualified and currently uses QMI 2569 on > 75% of the Class V products produced in the Palm Bay assembly location.

Impact on fit, form, function, quality & reliability:

The Henkel QMI 2569 silver glass adhesive will have no impact to the form, fit, function, or interchangeability of the product. Qualification plans for a change in material (die attach) are designed using MIL-PRF-38535, JEDEC, and other applicable industry standards to confirm there is no impact to form, fit, function, or interchangeability of the product. The reliability qualification summary and affected products list are included for reference. The remainder of the manufacturing operations (wafer fabrication, package level electrical testing, Q/TCI testing, shipment, etc.) will continue to be processed to previously established conditions and systems.

Product Identification:

Product affected by this change is identifiable via Intersil's internal traceability system. Customers can expect to receive product manufactured with either qualified die attach material (QMI 2569M or JM7000).

Qualification status: Complete, see attached

Sample availability: 60 days after receipt of request Device material declaration: Available upon request

Questions or requests pertaining to this change notice, including additional data or samples, must be sent to Intersil within 30 days of the publication date.

For additional information regarding this notice, please contact your regional change coordinator (below)					
Americas: PCN-US@INTERSIL.COM	Europe: PCN-EU@INTERSIL.COM	Japan: PCN-JP@INTERSIL.COM	Asia Pac: PCN-APAC@INTERSIL.COM		



Appendix A - Affected Products List

5962-85016023A	5962-87677012A	84065023A	HI1-674ATD/883
5962-8512704XA	5962-87677012AR4573	8406602XA	HI4-0546/883
5962-85131013A	5962-88502012A	85015013A	HI4-0547/883
5962-85131013AS2035	5962-89635012A	CDP1802ACD3	HI4-0548/883
5962-85131023A	5962-89636012A	HA4-5002/883	HI4-5051/883
5962-85131073A	77052012A	HI1-574AJD-5	HM1-6617/883
5962-85131092A	7705201EC	HI1-574AKD-5	HM1-6642B/883
5962-86716012A	77052022A	HI1-574ASD-2	HS1-3182-8
5962-86860012A	78029013A	HI1-574ATD-2	HS1-3182-9+
5962-8687901EA	84065013A	HI1-674AKD-5	HS4-3182-8

Appendix B - Qualification Results

INTERSIL Corporation

Group D Attributes Data In Accordance with MIL-PRP-38535

 Lot ID:
 50582T02-G3L6JBA
 Assembly Site: HSS

 Lot ID'S Combined:
 Fackage Code: XEJ

 Date Code(s):
 X1607ABBD
 Die Attach: As GLASS

 INTERSIL Part #:
 HS9-26CLV31RH-8
 Lead Pinish: C

 Marketing Part #:
 5962F9666302QXC
 Fab Quarter: 15B

Description Method SSSS SS/C Rejects Test Date Subgroup Comments ----PHYSICAL DIMENSIONS 2016 LEAD FATIGUE 2004 N/A 015/0 0 13 APRIL 16
 LEAD FATIGUR
 2004
 N/A
 045/0

 +25C INITIAL ELECTRICALS
 N/A
 N/A
 015/0

 THERMAL SHOCK
 1011
 N/A
 015/0

 TEMP CYCLE
 1010
 N/A
 015/0
 0 19 APRIL 16 0 10 MARCH 16 0 14 MARCH 16 D3 0 18 MARCH 16 MOISTURE RESISTANCE 1004 N/A 015/0 VISUAL EXAM 1004 N/A 015/0 D3 0 14 APRIL 16 D3 0 15 APRIL 16 +25C POST ELECTRICALS N/A N/A 015/0 0 15 APRIL 16 D31014 N/A 015/0 FINE LEAK 1014 N/A 015/0 0 20 APRIL 16 DЗ 0 20 APRIL 16 D3 GROSS LEAK +25C INITIAL ELECTRICALS N/A N/A 015/0 0 10 MARCH 16 D4 MECHANICAL SHOCK 2002 N/A 015/0 D 04 APRIL 16 VIBRATION VAR. FREQ. 2007 N/A 015/0 0 04 APRIL 16 CONSTANT ACCELERATION 2001 N/A 015/0 0 06 APRIL 16 1014 N/A 015/0 1014 N/A 015/0 1011 N/A 015/0 FINE LEAK 0 07 APRIL 16 GROSS LEAK 0 07 APRIL 16 VISUAL EXAM 0 08 APRIL 16 +25C POST ELECTRICALS N/A N/A 015/0 0 12 APRIL 16 SALT ATMOSPHERE 1009 N/A 015/0 VISUAL EXAM 1009 N/A 015/0 0 14 APRIL 16 0 14 APRIL 16 D5 FINE LEAK 1014 N/A 015/0 0 15 APRIL 16 D5 GROSS LEAK 1014 N/A 015/0 0 16 APRIL 16 INTERNAL WATER VAPOR 1018 N/A 003/0 0 25 APRIL 16 De. LEAD FINISH 0 18 APRIL 16 П7 2025 N/A 015/0