



## Power MOSFET

<b>PRODUCT SUMMARY</b>	
V <sub>DS</sub> (V)	-100
R <sub>DS(on)</sub> ( $\Omega$ )	V <sub>GS</sub> = -10 V   0.30
Q <sub>g</sub> max. (nC)	38
Q <sub>gs</sub> (nC)	6.8
Q <sub>gd</sub> (nC)	21
Configuration	Single



### FEATURES

- Dynamic dv/dt rating
- Repetitive avalanche rated
- P-channel
- 175 °C operating temperature
- Fast switching
- Ease of paralleling
- Simple drive requirements
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



### Note

\* This datasheet provides information about parts that are RoHS-compliant and / or parts that are non-RoHS-compliant. For example, parts with lead (Pb) terminations are not RoHS-compliant. Please see the information / tables in this datasheet for details.

### DESCRIPTION

Third generation power MOSFETs from Vishay provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.

The TO-220AB package is universally preferred for all commercial-industrial applications at power dissipation levels to approximately 50 W. The low thermal resistance and low package cost of the TO-220AB contribute to its wide acceptance throughout the industry.

<b>ORDERING INFORMATION</b>	
Package	TO-220AB
Lead (Pb)-free	IRF9530PbF SiHF9530-E3
SnPb	IRF9530 SiHF9530

### ABSOLUTE MAXIMUM RATINGS (T<sub>C</sub> = 25 °C, unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNIT
Drain-Source Voltage	V <sub>DS</sub>	-100	V
Gate-Source Voltage	V <sub>GS</sub>	± 20	
Continuous Drain Current	V <sub>GS</sub> at - 10 V	- 12	A
		-8.2	
Pulsed Drain Current <sup>a</sup>	I <sub>DM</sub>	-48	
Linear Derating Factor		0.59	W/°C
Single Pulse Avalanche Energy <sup>b</sup>	E <sub>AS</sub>	400	mJ
Repetitive Avalanche Current <sup>a</sup>	I <sub>AR</sub>	-12	A
Repetitive Avalanche Energy <sup>a</sup>	E <sub>AR</sub>	8.8	mJ
Maximum Power Dissipation	P <sub>D</sub>	88	W
Peak Diode Recovery dV/dt <sup>c</sup>	dV/dt	- 5.5	V/ns
Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>stg</sub>	-55 to +175	°C
Soldering Recommendations (Peak temperature) <sup>d</sup>	for 10 s	300	
Mounting Torque	6-32 or M3 screw	10	lbf · in
		1.1	N · m

### Notes

- Repetitive rating; pulse width limited by maximum junction temperature (see fig. 11).
- V<sub>DD</sub> = -25 V, starting T<sub>J</sub> = 25 °C, L = 4.2 mH, R<sub>g</sub> = 25 Ω, I<sub>AS</sub> = -12 A (see fig. 12).
- I<sub>SD</sub> ≤ -12 A, dI/dt ≤ 140 A/μs, V<sub>DD</sub> ≤ V<sub>DS</sub>, T<sub>J</sub> ≤ 175 °C.
- 1.6 mm from case.

**THERMAL RESISTANCE RATINGS**







PARAMETER	SYMBOL	TYP.	MAX.	UNIT
Maximum Junction-to-Ambient	$R_{thJA}$	-	62	$^{\circ}\text{C}/\text{W}$
Case-to-Sink, Flat, Greased Surface	$R_{thCS}$	0.50	-	
Maximum Junction-to-Case (Drain)	$R_{thJC}$	-	1.7	


**SPECIFICATIONS ( $T_J = 25 \text{ }^{\circ}\text{C}$ , unless otherwise noted)**

PARAMETER	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT	
<b>Static</b>								
Drain-Source Breakdown Voltage	$V_{DS}$	$V_{GS} = 0 \text{ V}$	$I_D = -250 \mu\text{A}$	-100	-	-	V	
$V_{DS}$ Temperature Coefficient	$\Delta V_{DS}/T_J$	Reference to $25 \text{ }^{\circ}\text{C}$ , $I_D = -1 \text{ mA}$		-	-0.10	-	$\text{V}/\text{ }^{\circ}\text{C}$	
Gate-Source Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}$	$I_D = -250 \mu\text{A}$	-2.0	-	-4.0	V	
Gate-Source Leakage	$I_{GSS}$	$V_{GS} = \pm 20 \text{ V}$		-	-	$\pm 100$	nA	
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = -100 \text{ V}$ , $V_{GS} = 0 \text{ V}$		-	-	-100	$\mu\text{A}$	
		$V_{DS} = -80 \text{ V}$ , $V_{GS} = 0 \text{ V}$ , $T_J = 150 \text{ }^{\circ}\text{C}$		-	-	-500		
Drain-Source On-State Resistance	$R_{DS(on)}$	$V_{GS} = -10 \text{ V}$	$I_D = -7.2 \text{ A}^b$	-	-	0.30	$\Omega$	
Forward Transconductance	$g_{fs}$	$V_{DS} = -50 \text{ V}$ , $I_D = -7.2 \text{ A}^b$		3.7	-	-	S	
<b>Dynamic</b>								
Input Capacitance	$C_{iss}$	$V_{GS} = 0 \text{ V}$ , $V_{DS} = -25 \text{ V}$ , $f = 1.0 \text{ MHz}$ , see fig. 5		-	860	-	pF	
Output Capacitance	$C_{oss}$			-	340	-		
Reverse Transfer Capacitance	$C_{rss}$			-	93	-		
Total Gate Charge	$Q_g$	$V_{GS} = -10 \text{ V}$	$I_D = -12 \text{ A}$ , $V_{DS} = -80 \text{ V}$ , see fig. 6 and 13 <sup>b</sup>	-	-	38	nC	
Gate-Source Charge	$Q_{gs}$			-	-	6.8		
Gate-Drain Charge	$Q_{gd}$			-	-	21		
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = -50 \text{ V}$ , $I_D = -12 \text{ A}$ , $R_g = 12 \Omega$ , $R_D = 3.9 \Omega$ , see fig. 10 <sup>b</sup>		-	12	-	ns	
Rise Time	$t_r$			-	52	-		
Turn-Off Delay Time	$t_{d(off)}$			-	31	-		
Fall Time	$t_f$			-	39	-		
Internal Drain Inductance	$L_D$	Between lead, 6 mm (0.25") from package and center of die contact		-	4.5	-	nH	
Internal Source Inductance	$L_S$			-	7.5	-		
Gate Input Resistance	$R_g$	$f = 1 \text{ MHz}$ , open drain		0.4	-	3.3	$\Omega$	
<b>Drain-Source Body Diode Characteristics</b>								
Continuous Source-Drain Diode Current	$I_S$	MOSFET symbol showing the integral reverse p -n junction diode		-	-	-12	A	
Pulsed Diode Forward Current <sup>a</sup>	$I_{SM}$			-	-	-48		
Body Diode Voltage	$V_{SD}$	$T_J = 25 \text{ }^{\circ}\text{C}$ , $I_S = -12 \text{ A}$ , $V_{GS} = 0 \text{ V}^b$		-	-	-6.3	V	
Body Diode Reverse Recovery Time	$t_{rr}$	$T_J = 25 \text{ }^{\circ}\text{C}$ , $I_F = -12 \text{ A}$ , $dI/dt = 100 \text{ A}/\mu\text{s}^b$		-	120	240	ns	
Body Diode Reverse Recovery Charge	$Q_{rr}$			-	0.46	0.92	$\mu\text{C}$	
Forward Turn-On Time	$t_{on}$	Intrinsic turn-on time is negligible (turn-on is dominated by $L_S$ and $L_D$ )						


**Notes**

- a. Repetitive rating; pulse width limited by maximum junction temperature (see fig. 11).  
b. Pulse width  $\leq 300 \mu\text{s}$ ; duty cycle  $\leq 2 \%$ .


**TYPICAL CHARACTERISTICS** (25 °C, unless otherwise noted)

**Fig. 1 -Typical Output Characteristics,  $T_C = 25 \text{ }^{\circ}\text{C}$** 

**Fig. 4 -Normalized On-Resistance vs. Temperature**

**Fig. 2 - Typical Output Characteristics,  $T_C = 175 \text{ }^{\circ}\text{C}$** 

**Fig. 5 -Typical Capacitance vs. Drain-to-Source Voltage**

**Fig. 3 -Typical Transfer Characteristics**

**Fig. 6 -Typical Gate Charge vs. Gate-to-Source Voltage**






91076\_07

 $- V_{SD}$ , Source-to-Drain Voltage (V)

91076\_09






 $T_C$ , Case Temperature (°C)
**Fig. 7 -Typical Source-Drain Diode Forward Voltage**
**Fig. 9 -Maximum Drain Current vs. Case Temperature**




91076\_08

 $- V_{DS}$ , Drain-to-Source Voltage (V)
**Fig. 8 -Maximum Safe Operating Area**

**Fig. 10a - Switching Time Test Circuit**

**Fig. 10b - Switching Time Waveforms**


91076\_11

 $t_1$ , Rectangular Pulse Duration (s)
**Fig. 11 - Maximum Effective Transient Thermal Impedance, Junction-to-Case**



**Fig. 12a - Unclamped Inductive Test Circuit**

**Fig. 12b - Unclamped Inductive Waveforms**

**Fig. 12c - Maximum Avalanche Energy vs. Drain Current**

**Fig. 13a - Basic Gate Charge Waveform**

**Fig. 13b - Gate Charge Test Circuit**



**Fig. 14 -For P-Channel**

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see [www.vishay.com/ppg?91076](http://www.vishay.com/ppg?91076).

### TO-220-1



DIM.	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
A	4.24	4.65	0.167	0.183
b	0.69	1.02	0.027	0.040
b(1)	1.14	1.78	0.045	0.070
c	0.36	0.61	0.014	0.024
D	14.33	15.85	0.564	0.624
E	9.96	10.52	0.392	0.414
e	2.41	2.67	0.095	0.105
e(1)	4.88	5.28	0.192	0.208
F	1.14	1.40	0.045	0.055
H(1)	6.10	6.71	0.240	0.264
J(1)	2.41	2.92	0.095	0.115
L	13.36	14.40	0.526	0.567
L(1)	3.33	4.04	0.131	0.159
Ø P	3.53	3.94	0.139	0.155
Q	2.54	3.00	0.100	0.118

ECN: X15-0364-Rev. C, 14-Dec-15  
DWG: 6031


#### Note

- $M^*$  = 0.052 inches to 0.064 inches (dimension including protrusion), heatsink hole for HVM

Package Picture

ASE

Xi'an





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.