ZA2BS934

red Ø30 Emergency stop, switching off head trigger and latching key release





	ľ	V	la	П	n
--	---	---	----	---	---

Range of Product	Harmony XAC
Product or Component Type	Head for emergency switching off push-button
Sale per indivisible quantity	1

Complementary

Marking	Unmarked	
Cap/operator or lens colour	Red	
Product Compatibility	XACA	
Mounting Location	Front of enclosure	
Net Weight	0.13 lb(US) (0.06 kg)	
Overvoltage category	Class II IEC 61140	

Environment

Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
IK degree of protection	IK08 EN 50102	
Standards	UL 508 EN/IEC 60947-5-5 CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60204-32	
Vibration resistance	15 gn 10500 Hz)IEC 60068-2-6	

Ordering and shipping details

Category	18073 - SPARE PARTS DISCOUNT I	
Discount Schedule	CP2	
GTIN	3389110591774	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.47 oz (70 g)	
Returnability	Yes	
Country of origin	FR	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.65 in (4.2 cm)	
Package 1 width	2.05 in (5.2 cm)	
Package 1 Length	3.98 in (10.1 cm)	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	

Package 2 Weight	24.80 oz (703 g)
Package 2 Height	2.56 in (6.5 cm)
Package 2 width	7.09 in (18 cm)
Package 2 Length	5.91 in (15 cm)
Unit Type of Package 3	S01
Number of Units in Package 3	40
Package 3 Weight	6.67 lb(US) (3.027 kg)
Package 3 Height	5.91 in (15 cm)
Package 3 width	5.91 in (15 cm)
Package 3 Length	15.75 in (40 cm)

Offer Sustainability

Green Premium product
WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
☑ REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope) [™] EU RoHS Declaration
Yes
Yes
₫Yes
[☑] China RoHS Declaration
Product Environmental Profile
End Of Life Information

Contractual warranty

	Warranty	18 months
--	----------	-----------