Stranded SXL Automotive Primary Hook Up Wire from Remington Industries is ideal for higher temperature, more rugged circuit wiring applications that specify SAE J1128 requirements, such as automotive, electric motor, and generator applications. The multi conductor wire is made from bare copper that offers high quality performance for most electrical applications. Additionally, the XLPE insulation protects the wire against abrasion, chemicals, fuels, oils, and solvents, while also remaining flexible enough to fit wherever it might be needed. This hook up wire is available in several wire gauges (from 12 to 20 AWG) to meet your specific requirements. It is also available in a variety of bold colors (see below) to allow for easy circuit identification, as well as numerous spool sizes (see below) for your convenience.

Conductor Material: Bare Copper

Voltage Rating: 60 V

• Type: SAE J1128 SXL Hook Up Wire, Stranded

Temperature Rating: -40°C (-40°F) to 125°C (257°F)

Insulation Material: Cross-Linked Polyethylene (XLPE / PEX / XPE)

- Colors Available: Black, Blue, Brown, Gray, Green, Orange, Red, Violet, White, Yellow
- Spool Sizes Available: 25 ft, 100 ft, 250 ft, 500 ft, 1000 ft, 2500 ft, 5000 ft
- Also available in pre-built kits (6 or 10 different colors / 25 ft or 100 ft per spool)
- Specifications: Ford ESB-M1L85-A/86-A, & Chrysler MS-5919
- RoHS & REACH Compliant



	OVERALL DIAMETER STRANDED WIRE DIAMETER				provide essential, high quality wire for engineering projects, educational science projects, coil winding, and electronics applications. Some of our many wire services include the following: - Wire Re-Packaging - Bifilar & Trifilar Windings - Wire Processing - Coil Winding - Wire Procurement Services
PART NUMBER	WIRE GAUGE	STRANDING	WIRE DIAMETER	OVERALL DIAMETER	If you have any questions or need any information about our Wire Services, feel free to contact us! It only takes one call to get experienced
12STRSXL	12 AWG	19/25	0.088"	0.161"	assistance. Contact us by phone: (815) 385-1987 Contact us by email: sales@remingtonindustries.com
14STRSXL	14 AWG	19/27	0.069"	0.141"	Sales@remmgtonmuustnes.com
16STRSXL	16 AWG	19/29	0.056"	0.118"	DATE ISS. REVISION BY Drawn by: AG 5/25/21 Drawing rev.:
18STRSXL	18 AWG	16/30	0.048"	0.107"	Remington
20STRSXL	20 AWG	7/28	0.038"	0.096"	3521 N. Chapel Hill Rd Johnsburg, IL 60051 USA remingtonindustries.com

SXL Hook Up Wire Stranded **Data Sheet**

Remington Industries

is proud to offer our

Custom Wire Services

procure wire of all kinds makes us the perfect partner for wire purchasing and custom wire services. We are proud to

Our exclusive inventory of

in-stock wire and ability to