

1.75mm PLA (750g) – White

SKU: FIT0409



INTRODUCTION

This is 1.75mm PLA filament which is commonly used by reprap, Makerbot, Mendel, Huxley UP! Printer, WeisTek and Thingo-matic 3D printers. It comes with one spool that can be easily attached on 3D printer.

PLA is a wonderful filament. It is the most environmentally friendly material available for this type of 3D printing, and it comes in a wide range of colors.

Polylactic acid or polylactide (PLA) is a thermoplastic aliphatic polyester derived from renewable resources, such as corn starch, tapioca roots, chips or starch, or sugarcane. It can biodegrade under certain conditions.

As the extrusion head temperature will vary from 3D printer to 3D printer design, temperature differences will affect the result of your print, we suggest PLA use an optimal temperature range of 185°C to 200°C. Please make the appropriate adjustments to temperature before you print with PLA, some testing might be required to find your optimal print settings.

SPECIFICATION

Tensile Strength@Yield 46Mpa Tensile Elongation@Break 20% Flexural Strength 70Mpa Flexural Modulus 3212Mpa Notched lzod lmpact(23°C) $5.2kj/m^2$ HDT@66psi 58°C density 1.31g/cm3 MFR 10-14g/10min 1.75±0.1mm Accuracy

750g

SHIPPING LIST

Weight

• 1.75mm PLA (750g) - White x1