XZCE13M785M

Adaptor, metal, tapped hole Pg 13.5, for male connector, 7/8" 16UN, 5 wire



Main Accessory / separate 5-wire connector adaptor part designation Accessory / separate Cabling accessories part category Accessory / Separate Connector adaptor Part Type Cable composition 5 x 1 mm² Pg 13.5 Thread type Line Rated Current 6 A

Complementary

Cable length	3.94 in (100 mm)	
Total number of wires	5	
Electrical connection	1 male connector 5 straight	
Cable connector fixing	Screw-on	
Body Material	Metal	
Insulation resistance	> 1000000000 Ohm	
Maximum resistance across terminals	5000 mOhm	
[Ue] rated operational voltage	250 V AC 300 V DC	
Net Weight	0.11 lb(US) (0.05 kg)	

Environment

IP Degree of Protection	IP67	
Ambient Air Temperature for Operation	-13176 °F (-2580 °C)	

Ordering and shipping details

Category	22483-MACHINE CABLES	
Discount Schedule	DS3	
GTIN	3389110868760	
Nbr. of units in pkg.	1	
Package weight(Lbs)	1.66 oz (47.0 g)	
Returnability	No	
Country of origin	PL	

Packing Units


Unit Type of Package 1	PCE	
Package 1 Height	1.57 in (4 cm)	
Package 1 width	1.77 in (4.5 cm)	
Package 1 Length	5.91 in (15 cm)	
Unit Type of Package 2	S02	
Number of Units in Package 2	50	
Package 2 Weight	6.40 lb(US) (2.905 kg)	
Package 2 Height	5.91 in (15 cm)	

Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₽¥Yes
Contractual warranty	
Warranty	18 months

Product data sheet Dimensions Drawings

XZCE13M785M


Dimensions



Product data sheet Connections and Schema

XZCE13M785M

Connections and Schemes



BN : Brown BK : Black BU : Blue

Y/G : Yellow / Green

WH : White