



SOLDER CUP INTERNAL  $\phi$   
 SIGNAL CONTACTS = 20 AWG MAX  
 20 AMP =  $\phi$ 2.70 (12AWG MAX)  
 40 AMP =  $\phi$ 4.60 (8AWG MAX)



**NOTE:**

**MATERIAL**  
 HOUSING PBT UL94V-0, BLACK  
 FLANGE PBT UL94V-0, BLACK  
 CONTACT BRASS, PLATING P/N KEY BELOW  
 SHELL STEEL, NICKEL  
 O-RING SILICONE  
 SEALING COMPOUND EPOXY  
 HARDWARE BRASS; NICKEL PLATED

**ELECTRICAL**  
 SIGNAL CONTACT RATED CURRENT 5A  
 POWER CONTACT RATED CURRENT P/N KEY BELOW  
 VOLTAGE 1000 VAC 1 MIN  
 INSULATOR RESISTANCE 5 GOhms MIN.  
 SIGNAL CONTACT RESISTANCE 10 mOhms MAX.  
 POWER CONTACT RESISTANCE 2.0 mOhms MAX.  
 WATER PROOF IP67

**ENVIRONMENT**  
 OPERATION TEMPERATURE -25°C TO +85°C

**CDFS9W4203LYYY**

SERIES \_\_\_\_\_  
 CDF = COMBO DSUB FLANGE  
 CONTACT TYPE \_\_\_\_\_  
 S = SOLDER CUP  
 POSITION \_\_\_\_\_  
 9W4  
 GENDER \_\_\_\_\_  
 2 = FEMALE  
 POWER CONTACT AMPERAGE \_\_\_\_\_  
 2 = 20 AMPS  
 4 = 40 AMPS  
 HARDWARE OPTIONS \_\_\_\_\_  
 1 = 4-40 THREADED INSERTS/4-40 JACKSCREWS  
 CONTACT PLATING OPTIONS \_\_\_\_\_  
 1 = GOLD FLASH  
 2 = 30u" GOLD PLATING

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: J. KADEL  
 DATE: 04/22/2020

**TOLERANCES**  
 X. ±0.40  
 .X ±0.30  
 .XX ±0.20  
 .XXX ±0.10

UNITS = mm

DO NOT SCALE FROM DRAWING

**NorComp**

SCALE: NTS	SHEET 1	OF 1	REV 1
DWG NO.		CDFS9W4203LYYY	