


Powerex, Inc., 200 E. Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272


### Intellimod™ Module

Application Specific IPM  
15 Amperes/1200 Volts



Outline Drawing and Circuit Diagram

Dimensions	Inches	Millimeters
A	4.06 +0/-0.02	103.0+0/-0.4
B	2.87 +0/-0.02	73.0 +0/-0.4
C	0.35	9.0
D	0.10	2.5
E	3.11	79.0
F	3.74±0.01	95±0.2
G	1.32	33.5
H	0.95	24.0
J	0.87	22.0
K	0.08	2.0
L	0.24	6.0
M	0.02 Sq.	0.5 Sq.
N	2.72	69.0
P	2.13	54.0
Q	1.54±0.01	39.0±0.2
R	0.95	24.0
S	0.26	6.5
T	0.35	9.0
U	0.59	15.0
V	0.37	9.5
W	0.08	2.0
X	0.12	3.0



#### Description:

Powerex Application Specific IPMs (ASIPMs) are intelligent power modules that integrate power devices, gate drive and protection circuitry in a compact package for use in small inverter applications up to 20kHz. Use of application specific HVICs allow the designer to reduce inverter size and overall design time.

#### Features:

- Rectifier Bridge for 3-phase AC-to-DC Power Conversion
- 3-phase IGBT Inverter Bridge
- Integrated HVICs for Gate Drive, Protection and System Control Functions
- Built-in Thermistor
- Direct Connection to DSP/CPU

#### Applications:

- Smart Motors
- General Purpose Inverters
- Small Motor Control

#### Ordering Information:

PS12036 is a 1200V, 15 Ampere Application Specific Power Module.



Powerex, Inc., 200 E. Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

**PS12036**

**Intellimod™ Module**

**Application Specific IPM**

15 Amperes/1200 Volts

**Absolute Maximum Ratings,  $T_j = 25^\circ\text{C}$  unless otherwise specified**

Characteristics	Symbol	PS12036	Units
Power Device Junction Temperature*	$T_j$	-20 to 125	°C
Storage Temperature	$T_{stg}$	-40 to 125	°C
Case Operating Temperature (See $T_C$ Measure Point Illustration)	$T_C$	-20 to 100	°C
Mounting Torque, M3.5 Mounting Screws	—	11.25	in-lb
Module Weight (Typical)	—	127	Grams
Isolation Voltage**	$V_{ISO}$	2500	Volts

\*The indicated values are specified considering the safe operation of all the parts within the ASIPM. The maximum rating for the ASIPM power chips (IGBT & FWDi) is  $T_j < 150$ .

\*\*60 Hz sinusoidal AC applied between all terminals and the base plate for 1 minute.

**IGBT Inverter Sector**

Supply Voltage (Applied between P2 - N2)	$V_{CC}$	900	Volts
Supply Voltage, Surge (Applied between P2 - N2, Surge-Value)	$V_{CC(\text{surge})}$	1000	Volts
Each IGBT Collector-Emitter Static Voltage (Applied between P2-U·V·W, U·V·W-N2)	$V_P$ or $V_N$	1200	Volts
Each IGBT Collector-Emitter Switching Voltage (Applied between P2-U·V·W, U·V·W-N2 (Pulse))	$V_{P(S)}$ or $V_{N(S)}$	1200	Volts
Each IGBT Collector Current, $T_C = 25^\circ\text{C}$ , "( )" means $I_C$ Peak Value	$\pm I_C (\pm I_{CP})$	$\pm 15 (\pm 30)$	Amperes

**Converter Sector**

Repetitive Peak Reverse Voltage	$V_{RRM}$	1600	Volts
Recommended AC Input Voltage	$E_a$	440	Vrms
DC Output Current (3-phase Rectifying Circuit)	$I_O$	12	A
Surge (Non-repetitive) Forward Current (1 Cycle at 60Hz, Peak Value Non-repetitive)	$I_{FSM}$	120	A
$I^2t$ for Fusing (Value for One Cycle of Surge Current)	$I^2t$	60	$\text{A}^2\text{s}$

**Control Sector**

Supply Voltage	$V_D, V_{DB}$	-0.5 ~ 20	Volts
Input Signal Voltage	$V_{CIN}$	-0.5 ~ 7.5	Volts
Fault Output Supply Voltage	$V_{FO}$	-0.5 ~ 7.5	Volts
Fault Output Current	$I_{FO}$	15	mA
DC-link IGBT Current Signal Amp Output Current	$I_{AMP}$	1	mA

**PS12036**

**Intellimod™ Module**


**Application Specific IPM**

15 Amperes/1200 Volts

### Electrical and Mechanical Characteristics, $T_j = 25^\circ\text{C}$ unless otherwise specified

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
<b>IGBT Inverter Sector</b>						
Collector-Emitter Saturation Voltage	$V_{CE(\text{sat})}$	$I_C = 15\text{A}, T_j = 25^\circ\text{C}, V_D = V_{DB} = 15\text{V},$ Input = ON (Shunt Voltage Drop Not Included)	—	—	3.6	Volts
Diode Forward Voltage	$V_{EC}$	$T_j = 25^\circ\text{C}, -I_C = 15\text{A}$	—	—	3.5	Volts
Converter Diode Voltage	$V_{FR}$	$T_j = 25^\circ\text{C}, I_{FR} = 12\text{A}$	—	—	1.7	Volts
Converter Diode Reverse Current	$I_{RRM}$	$V_R = V_{RRM}, T_j = 125^\circ\text{C}$	—	—	8.0	mA
Switching Times	$t_{on}$	1/2 Bridge Inductive, Input = $5\text{V} \leftrightarrow 0\text{V}$ ,	0.3	1.2	2.0	$\mu\text{s}$
	$t_{C(on)}$	$V_{CC} = 600\text{V}, I_C = 15\text{A}, T_j = 125^\circ\text{C},$	—	0.5	1.4	$\mu\text{s}$
	$t_{off}$	$V_D = 15\text{V}, V_{DB} = 15\text{V}$	—	2.2	4.0	$\mu\text{s}$
	$t_{C(off)}$	Note: $t_{on}, t_{off}$ include delay time of	—	0.9	1.6	$\mu\text{s}$
FWDi Reverse Recovery Time	$t_{rr}$	the internal control circuit.	—	0.2	—	$\mu\text{s}$
Short-circuit Endurance (Output, Arm, and Load Short-circuit Modes)		$@V_{CC} \leq 800\text{V}, \text{Input} = 5\text{V} \rightarrow 0\text{V}$ (One-shot), $-20^\circ\text{C} \leq T_j(\text{start}) \leq 125^\circ\text{C},$ $13.5\text{V} \leq V_D = V_{DB} \leq 16.5\text{V}$	<ul style="list-style-type: none"> <li>• No Destruction</li> <li>• <math>F_O</math> Output by Protection Operation</li> </ul>			
Switching SOA		$@V_{CC} \leq 800\text{V}, \text{Input} = 5\text{V} \rightarrow 0\text{V},$ $T_j \leq 150^\circ\text{C}, I_C < \text{OC Trip Level},$ $13.5\text{V} \leq V_D = V_{DB} \leq 16.5\text{V}$	<ul style="list-style-type: none"> <li>• No Destruction</li> <li>• No Protecting Operation</li> <li>• No <math>F_O</math> Output</li> </ul>			

$T_C$  Measure Point





Powerex, Inc., 200 E. Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

**PS12036**

**Intellimod™ Module**

**Application Specific IPM**

15 Amperes/1200 Volts

### Electrical and Mechanical Characteristics, $T_j = 25^\circ\text{C}$ unless otherwise specified

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units	
<b>Control Sector</b>							
Circuit Current (Average)	$I_D$	$T_j = 25^\circ\text{C}, V_D = 15\text{V}, V_{IN} = 5\text{V}$	—	—	50	mA	
	$I_{DB}$	$T_j = 25^\circ\text{C}, V_D = V_{DB} = 15\text{V}, V_{IN} = 5\text{V}$	—	—	5	mA	
Input ON Threshold Voltage	$V_{th(on)}$		0.8	1.4	2.0	Volts	
Input OFF Threshold Voltage	$V_{th(off)}$		2.5	3.0	4.0	Volts	
Input Pull-up Resistor	$R_i$	Applied between Input Terminal-inside Power Supply	—	50	—	kΩ	
PWM Input Frequency	$f_{PWM}$	$T_C \leq 100^\circ\text{C}, T_j \leq 125^\circ\text{C}$	—	10	15	kHz	
Arm Shoot-through Blocking Time*	$t_{DEAD}$	Relates to Corresponding Inputs $T_C = -20^\circ\text{C} \sim 100^\circ\text{C}$	4.0	—	—	μS	
Input Interlock Sensing	$t_{int}$	Relates to Corresponding Input	—	100	—	ns	
Inverter DC-link IGBT Current	$V_{amp\ 100\%}$	$I_C = I_{OP}(100\%), V_D = 15\text{V}, T_j = 25^\circ\text{C}$	1.5	2.0	2.5	Volts	
Sense Voltage Output Signal**	$V_{amp\ 200\%}$	$I_C = I_{OP}(200\%), V_D = 15\text{V}, T_j = 25^\circ\text{C}$	3.0	4.0	5.0	Volts	
Inverter DC-link IGBT Current	$V_{amp\ 250\%}$	$I_C = I_{OP}(250\%), V_D = 15\text{V}$	5.0	—	—	Volts	
Sense Voltage Output Limit**	$V_{amp\ 0\%}$	$I_C = I_{OP}(0\%), V_D = 15\text{V}$	—	50	100	mV	
Over-current Trip Level	$OC$		23.3	28.3	—	Amperes	
Over-current Delay Time	$t_{OC}$	$T_j = 25^\circ\text{C}$	—	10	—	μS	
Short-circuit Trip Level	$SC$		—	42.45	—	Amperes	
Short-circuit Delay Time	$t_{SC}$		—	2	—	μS	
	Trip Level	$UV_D$	11.0	12.0	12.75	Volts	
Supply Circuit	Reset Level	$UV_{Dr}$	11.5	12.5	13.25	Volts	
Under-voltage	Trip Level	$UV_{DB}$	$T_C = T_j = 25^\circ\text{C}$	10.1	10.8	11.6	Volts
Protection	Reset Level	$UV_{DBr}$		10.6	11.3	12.1	Volts
	Delay Time	$t_{dV}$	—	10	—	μS	
Fault Output Pulse Width***	$t_{FO}$	$T_j = 25^\circ\text{C}$	1.0	1.8	—	mS	
Fault Output Current***	$I_{FO(H)}$	Open Collector Output	—	—	1	μA	
	$I_{FO(L)}$		—	—	15	mA	
Thermistor Resistance	$R_{TO}$	$T_O = 25^\circ\text{C} (298\text{K})$	9.5	10	10.5	kΩ	
Material Constant****	$\beta$	$T_1 = 25^\circ\text{C}, T_2 = 50^\circ\text{C}$	—	3450	—	K	

\* The dead-time has to be set externally by the CPU; it is not part of the ASIPM internal functions.

\*\*Refer to the graph on next page.

\*\*\*Fault output signalling is given only when the internal OC, SC, and UV protection circuits are activated. The OC, SC and UV protection (and fault output) operate for the lower arms only. The OC and SC protection fault output is given in a pulse format while that of UV protection is maintained throughout the duration of the under-voltage condition.

$$****T = \frac{1}{\frac{1}{\beta} \cdot \ln \left[ \frac{R_T}{R_{TO}} \right] + \frac{1}{T_O}}$$

**PS12036**

**Intellimod™ Module**

**Application Specific IPM**


15 Amperes/1200 Volts

### Thermal Characteristics

Characteristic	Symbol	Condition	Min.	Typ.	Max.	Units
Junction to Case	$R_{th(j-c)Q}$	Each IGBT	—	—	2.1	°C/Watt
	$R_{th(j-c)D}$	Each FWDi	—	—	2.5	°C/Watt
	$R_{th(j-c)DR}$	Each Converter	—	—	2.5	°C/Watt
Contact Thermal Resistance	$R_{th(c-f)}$	Case to Fin Per Module. Thermal Grease Applied	—	—	0.05	°C/Watt

### Recommended Conditions for Use

Characteristic	Symbol	Condition	Min.	Typ.	Value	Units
Supply Voltage	$V_{CC}$	Applied across P2-N2 Terminals	—	600	800	Volts
Control Supply Voltage	$V_D$	Applied between $V_D$ -GND	13.5	15.0	16.5	Volts
	$V_{DB}$	Applied between CBU+ & CBU-, CBV+ & CBV-, CBW+ & CBW-	13.5	15.0	16.5	Volts
Control Supply dv/dt	$dV_D/dt, dV_{DB}/dt$		-1	—	1	$V/\mu s$
Input ON Voltage	$V_{CIN(on)}$	Applied between	0	—	0.8	Volts
Input OFF Voltage	$V_{CIN(off)}$	$U_P, V_P, W_P, U_N, V_N, W_N$ -GND	4.0	—	5.0	Volts
Module Case Operating Temperature	$T_C$		—	—	100	°C
PWM Input Frequency	$f_{PWM}$	$T_C \leq 100^\circ\text{C}, T_j \leq 125^\circ\text{C}$	—	—	15	kHz
Allowable Minimum Input On-pulse Width	$t_{xx}$		1	—	—	$\mu s$
Arm Shoot-through Blocking Time	$t_{DEAD}$	Relate to Corresponding Inputs	4.0	—	—	$\mu s$












**PS12036**

**Intellimod™ Module**










**Application Specific IPM**

15 Amperes/1200 Volts



**PS12036**

**Intellimod™ Module**  
**Application Specific IPM**  
 15 Amperes/1200 Volts




**PS12036**

**Intellimod™ Module**

**Application Specific IPM**

15 Amperes/1200 Volts



Functional Block Diagram

